

Product profile

6822

Mobile Full Page Printer



- Choice of portable or fixed-mount configurations
- Wireless printing via optional Bluetooth holder for portable and fixed-mount configurations
- Easy loading of up to 3-ply paper from internal or external paper trays
- 512k flash memory can store DBCS fonts such as Korean and Chinese
- Optional HHC holders and docks for Intermec CN3/e, CN4/e and CN70/e Series mobile computers
- Fast two-page-per-minute print time helps get the work done fast

The Intermec® 6822 printer produces high-quality customer invoices, receipts, load reports, transfers and other documents for route accounting applications. The real time accounting structure provided by the 6822 printer and Intermec handheld computers facilitates route delivery settlement and ensures customer information is always current.

Customers have the choice of portable or fixed-mount configurations depending on mobility requirements.

Portable

The Intermec 6822 printer provides flexibility and mobility. It features a handle for easy carrying and a compact tray which

holds enough paper for an entire day. A seat-mount strap is available to secure the printer in vehicles with bench seats. An optional, soft-sided carrying case provides a sealed compartment inside the case cover for storage of invoices.

Fixed Mount

The fixed mount model is ideal for applications where mounting the printer in a vehicle is preferred. The mobile computer holder can be mounted either to the side of the printer or remote from the printer, whichever is most convenient. Although the printer is safely mounted to the vehicle, a quick release feature allows one-step removal of the printer for swapping from one vehicle to another.

Application

Portable dot matrix receipt printer

Portable

Optional AC foot, Intermec CN3/e, CN4/e and CN70/e Series terminal holder top mount.

Physical Characteristics

Length: 38.1cm (15")
Width: 41.9cm (16.5")
Depth: 13cm (5.13")
Weight: 5.67kg (12.25 lbs.)

Portable with AC Foot**Physical Characteristics**

Length: 38.1cm (15")
Width: 48.3cm (19")
Depth: 13cm (5.13")
Weight: 5.67kg (12.25 lbs.)

Fixed Mount

- Base is 32.5cm (12.75") x 35.5cm (14").
- Refer to the 6820 printer user's guide (961-019-013) for specific configurations for the following:
 - Custom with Intermec CN3/e, CN4/e and CN70/e Series terminal holder top mount

Physical Characteristics

Length: 36.8cm (14.5")
Width: 47cm (18.5")
Depth: 20.3cm (8")
Weight: 6.55kg (14.4 lbs.)

Environment

DC Operating Temperature: -20° to 60°C (-4° to 140°F)
AC Operating Temperature: -20° to 45°C (-4° to 113°F)
Storage Temperature: -30° to 70°C (-22° to 158°F)
Humidity: 5% - 95% (non-condensing)
Drop spec: .6m (2 ft.) drop to concrete (6822P only)

Power Supply

Vehicle: low amperage draw; protection from voltage irregularities
Lead Acid Battery: 12-volt standard cam-corder type. Full charge will print dozens of tickets. Time to recharge is one hour.
AC Adapter: 115/230 volt

Print Specifications

Characteristics: Dot matrix, Bi-directional, Graphics capable
Print speed: 2 pages per minute
Print width (min/max): 7.5 inch/8.5 inch
Type styles: (char/line) Normal 80, Bold 40, Condensed 136, Bold condensed 68

Media

1 to 3-ply fan fold, 7.5" to 8.5" x 11", Carbonless, NCR paper with adhesive tacking on left border

Ribbon

- One color cartridge, black, 2,250,000 character life
- One color cartridge, purple, 3,750,000 character life

Regulatory Approvals

FCC Class B, CE mark

Options

- 6820 Developers Kit
- Bluetooth in Mobile Computer holder

Note

Some approvals and features may vary by country and may change without notice. Specs may vary based upon the specific configuration or features selected. Please check with your local Intermec sales office for further information.

Accessories

Universal Power Supply, Installation kits, data cables, Paper Tray, Soft sided carrying case, restraining straps

Warranty

One year, additional Medallion service available.

Safety Approvals

North America: UL and cUL Listed, UL 60950-1
Europe: EN 60950-1, e-Marked, EN 55022
Mexico: NYCE Certified, NOM 19
Other Countries: IEC 60950-1

EMC Approvals

US: FCC Class B
Canada: Industry Canada ICES-003 Class B
EU/EFTA countries: EN 55022 Class B, including telecom port and DC conducted emissions
EU/EFTA countries: e-mark

North America

6001 36th Avenue West
 Everett, Washington 98203
 Phone: (425) 348 2600
 Fax: (425) 355 9551

North Latin America

Mexico
 Phone: (+52) 55 52 41 48 00
 Toll Free NOLA:
 01800 490 4990

South Latin America

Brazil
 Phone: (+55) 11 3711 6770
 Fax: (+55) 11 5502 6780

Europe, Middle East & Africa

Reading, United Kingdom
 Phone: (+44) 118 923 0800
 Fax: (+44) 118 923 0801

Asia Pacific

Singapore
 Phone: (+65) 6303 2100
 Fax: (+65) 6303 2199

Media Sales

EMEA: (+31) 24 372 3167
 USA: (513) 874 5882
<http://intermec.custhelp.com>

Sales

Toll Free NA: (800) 934 3163
 Toll in NA: (425) 348 2726
 Freephone ROW:
 00800 4488 8844

OEM Sales

Phone: (425) 348 2762

Customer Service & Support

Toll Free NA: (800) 755 5505
 Toll in NA: (425) 356 1799
 EMEA: intermec.custhelp.com

Internet

www.intermec.com

Worldwide Locations

www.intermec.com/locations

