

Dolphin® 7450

Portable Data Terminal



Features

Microsoft® Windows® CE Platform - Portable convenience with full programming flexibility using Microsoft® eMbedded™ Visual Tools or Java™.

Integrated Pistol Grip Handle Design - Provides greater durability and preferred ergonomics for rapid, high volume scanning.

IQ Imaging™ with Advanced Linear Decoding (ALD)- Provides instant point-and-shoot 1D & 2D bar code scanning, captures signatures, and takes pictures.

ALR Laser Scanning Option - Provides long range scanning

Rugged IP-64 Construction - Operates in harsh environments and withstands rough treatment.

Multiple Keyboard Options - Intuitive, optimized layouts for various applications.

Cisco® 802.11b WLAN Communications with LEAP (Dynamic WEP) - Provides real time, pervasive information access and data transmission security.

Spectrum24® 802.11 FHSS WLAN Communications

Terminal Emulation Capability - Compatible with legacy applications.

Large 3.8" 1/4 VGA Display with Touch screen option - Backlit display provides easy viewing in most lighting conditions

Compact Flash Card Slot - Provides up to 256 MB of additional memory for data storage.

High Capacity 2700 mAh Battery Pack - Ensures long battery operation time with WLAN and scan-intensive applications.

The Dolphin® 7450 hand held computer offers the enhanced productivity features of the popular Dolphin® 7400 terminal with the added convenience of a pistol grip-style form factor for high volume scanning applications. The ergonomically friendly design makes the Dolphin 7450 ideally suited for most in-premise automatic data collection applications used in retail, distribution, warehousing, manufacturing, and transit industries.

The integrated pistol-grip handle provides comfortable ergonomics and intuitive point-and-shoot scanning for extended periods of use. Three backlit keypad options are available to enhance data entry efficiency in different industry-specific applications. Featuring the largest 1/4 VGA display in its product class, the 7450 provides crisp, easy-to-read application data and full content viewing, reducing the need for screen scrolling.

Bar code scanning performance is optimized through the use of HHP's patented area imaging technology, which provides omni-directional reading of all major 1D and 2D bar code symbologies. Data capture is further enhanced with the ability to incorporate photo images and signatures into ADC applications. An optional ALR laser scanner is also available for long-range scanning applications prevalent in warehousing and distribution centers.

Available in batch and with optional Cisco® 802.11b DSSS or Spectrum24® 802.11 FHSS wireless local area network (WLAN) connectivity, the Dolphin 7450 enables mobile workers to capture, process, and deliver data when and where it's needed. The Dolphin 7450 is equally durable, designed to withstand repeated five-foot drops to concrete and to meet IP-64 standards, fulfilling the needs of many industrial environments.

At the heart of the Dolphin 7450 lies the strength of Microsoft Windows® CE platform powered by the Intel StrongARM® 206 MHz processor. Configured with 32 MB RAM and 32 MB Flash memory, the 7450 provides ample, secure storage for current and emerging applications. An optional compact flash memory card is available to increase data storage up to 256 MB. Prolonged operation is ensured by the 7450's rechargeable 2700 mAh NiMH battery, which provides up to eight hours of continuous use between charges.

To learn how the Dolphin 7450 can work for you, contact us at any of the locations listed on the back or visit us at www.hhp.com.

Upgrade your image.



Dolphin® 7450 Specifications



Performance Specifications

Operating System:	Microsoft® Windows® CE
Application Development:	Windows architecture programmable with Microsoft® eMbedded™ Visual Tools (contains CE versions of Visual C++® and Visual Basic®) or Java™. Dolphin supports Insignia Solutions® Jeode™ Java Virtual Machine to run Java-based applications. RF connectivity software for Local Area Network systems and terminal emulation
CPU:	Intel® StrongARM™ RISC Processor, 206 MHz
Memory:	32 MB RAM, 32 MB non-volatile FLASH; optional Compact Flash card – up to 256 MB
Calendar/Clock:	Crystal-controlled
Wireless	
Local Area Network:	LAN RF Version Cisco 2.4GHz frequency within IEEE 802.11b industry standards, up to 11 Mbps throughput Spectrum24® 802.11 FHSS, up to 2Mbps throughput
Communications:	RS-232, IrDA

Data Inputs and Outputs

Image Engine Options:	LX: red or green aimer option scans from 2.0 to 15.0 in. (5.1 to 38.1 cm) LR: red or green aimer option scans from 1.9 to 9.4 in (4.8 to 23.9 cm) HD: red or green aimer scans from 1.6 to 3.9 in (4.1 to 9.9 cm) Non-scan option also available
1D Symbolologies Read:	Code 3 of 9, Interleaved 2 or 5, EAN, Codabar, Code 128, Plessey, Code 11, Code 93, UPC, RSS
2D Symbolologies Read:	PDF417, MaxiCode, Data Matrix, QR, RSS Composite, EAN.UCC, Aztec, OCR
Long Range Scanning:	ALR scanner option, 1D only; scans from 2.75 - 30 ft. (0.83 - 9.1 m) depending on bar code mil size
Keyboards:	Choice of 35-, 43-, or 56-keys, all backlit
Display:	3.8" ¼ VGA (240x 320 portrait mode), EL backlit, touch screen option available
Power:	2700 mAh NiMH battery
Status Indicator Lights:	Decode/good scan LEDs

Physical Specifications

Dimensions:	10.2" L x 3.45" W x 1.9" D at display (24.53 x 8.9 x 4.8 cm.), 2.7" W x 1.6" D at keyboard (6.9 x 4.0 cm.)
Weight:	28.8 oz (816 g) - Batch unit; 31.4 oz. (890 g) - RF unit
Materials:	Magnesium-alloy top housing and Polycarbonate ABS blend bottom housing and handle
Impact Resistance:	Survives multiple 5 ft. (1.5 m) drops to concrete
Environmental Sealing:	Designed to meet IP-64 standards for moisture and particle resistance
Operating Temperature:	14 to 122° F (-10 to 50° C)
Storage Temperature:	-22 to 176°F (-30 to 80°C)
Humidity:	95% humidity non-condensing

Electrical Static

Discharge:	15KV on all surfaces
Agency Approvals:	FCC Class B, CE, EN60950, R&TTE Directive

Peripherals and Accessories

HomeBase® Cradle:	Provides charging power to terminal while operational. Data transfer via infrared. Choose 120 V or 240 V AC power.
Mobile IntelliBase® Cradle:	Provides charging power to terminal while operational. Data transfer via infrared com port. Uses 12vDC or 48 vDC power
QuadCharger®	Simultaneously conditions and charges 1-4 batteries
Communication and Charging Cables:	Serial/charge cable; printer cables
Functional Case:	Slip-on style cover with belt clip
Holster:	Multi-purpose terminal holster, can be worn by user or wall/vehicle mounted

Microsoft® Windows® CE, eMbedded™ Visual Tools, Visual C++® and Visual Basic® are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries. Intel is a registered trademark of Intell Corporation. Java and all Java-based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc. in the U.S. and other countries.



Worldwide Offices

Offices Serving North America
Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 782 4263
sales@hhp.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 782 4263
sales@hhp.com

Offices Serving Europe, Middle East, and Africa
Europe
Tel: +31 (0) 40 29 01 600
euro_sales@hhp.com
United Kingdom
Tel: +44 (0) 1 925 240055
euro_sales@hhp.com
Ireland
Tel: +353 (0) 502 44007
euro_sales@hhp.com

France
Tel: +33 (0) 1 461 04111
euro_sales@hhp.com
Germany
Tel: +49 (0) 7 477 151377
euro_sales@hhp.com
Spain
Tel: +34 93 228 76 68
euro_sales@hhp.com

Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: +852 2511 3050/2511 3132
asia_sales@hhp.com
Japan
Tel: +813 52127392
asia_sales@hhp.com

Offices Serving Latin America
Naples, Florida
Tel: +1 239 263 7600
la-sales@hhp.com
São Paulo
Tel: +55 11 5016 3454
la-sales@hhp.com
Rio De Janiero
Tel: +55 21 2494 7060
la-sales@hhp.com

Web Site Address www.hhp.com

Hand Held Products, Inc. d/b/a HHP ("HHP") © 1999-2002. All rights reserved. Printed in the U.S.A.

Due to HHP's continuing product improvement programs, specifications and features herein are subject to change without notice.