CITIZEN

CLP 4081

For all your ticket, tag and barcoding needs



Thermal transfer and direct thermal printing High speed printing – up to 8 inches per second Internal rewinder and ribbon saver options

Heavy duty metal case

Better. Believe it.®

CITIZEN



CLP 4081

Ease of use

All of Citizen label and barcode printers are designed with ease of use in mind. The large metal case with large side panel and removable front cover makes access for ribbon and media loading

Dual Technology For High Quality

Printing with either thermal transfer technology on standard labels, card and plastic or using direct thermal transfer on to coated media, the CLP 4081 range creates crisp, detailed labels in all applications. The high quality printing means barcodes are clear and accurate and easy to read.

High Speed, High Performance

With a print speed of up to 8 inches per second, high volume label printing is not a problem. And for users who need to print small batches of labels quickly, the CLP 4081 range is more than capable.

Internal rewinding

On the CLP 4081R model, the internal rewinder makes printing batches of labels simplicity itself. There is no need for an external rewinder to take up the printed labels. They are simply fed back in to the printer for later use and the internal sensor on the printer also prevents the roll becoming too full.

Label peeling

The rewinder unit on the CLP 4081R model also allows users to operate the printer in the label peel mode, where the backing paper is pulled away from the labels and then stored inside the printer. The 'demand sensor' also means that the next label is not printed until the previous one has been removed from the printer.

Ribbon saving

The integral ribbon saver on the CLP 4081SR model reduces ribbon usage on labels with large areas of unprinted information. When enabled, the ribbon saving mechanism automatically stops the ribbon from advancing when there is no information to be printed. Naturally, the top-of-the-range CLP 4081SR also includes the rewinder and peeler options.

Windows 95, 98 and NT Compatibility.

Citizen's label printers are compatible with leading operating systems, assuring users of maximum flexibility and is committed to

developing its printer drivers to adapt to continually advancing technology.

LCD Control Panel

Users have no need to wonder whether our label printers are correctly set-up and ready to print. The LCD control panel displays easy-tounderstand messages about the status of the printer.

Options for Flexible Label Handling

Autocutter: Labels and continuous media are

automatically cut after printing.

Memory upgrade: 512K memory upgrade for larger labels

256K flash memory card: Allows label definitions, fonts and logos to be stored when the printer is switched off

Applications

- Product identification and inventory labelling.
- Filing and address labels.
- Dispatch, shipping and receiving labels.
- Point of sale shelf labels, product and warehouse labels.
- Medical labelling for patient records, samples, supplies and prescriptions.

ler	

Printhead	203 dpi (8 dots / mm)				
Print speed	8 inches / second, 203 mm/s				
Maximum print width	4.1 inches, 104 mm				
Maximum print length	40 inches, 1016 mm				
Maximum media width	4.65 inches, 118 mm				
Paper thickness	0.0026 - 0.01 inches 0.06 - 0.25 mm				
Media types	Roll or label (continuous, die cut, fanfold or ticket / tag)				
Media sensing	See-through and reflective sensors. Moveable media detection sensor				
Ribbon type	Wax, wax-resin or resin type				
Ribbon width	1 - 4.5 inches 25 - 114 mm				
Fonts	2 Scalable smooth fonts 6 - 48 pt 8 bitmap fonts, including OCR A,B Modified codepage 850				
Barcodes	Code 39,2 Of 5, EAN 8 EAN 13, Code 128 A/B/C, UPC A-E, Code 93, MSI, Plessey, Codabar, HIBC, AIAG, Logmars				
Internal Rewinder	No	Yes	Yes		
Peeler	No	Yes	Yes		
Ribbon Saver	No	No	Yes		
Interface	RS232C serial, 300 - 19,200 baud or RS422 serial				
Input buffer	12 Kb				
Memory	512Kb on board				
Memory Expansion	512 Kb expansion (total 1 Mb) 256K flash memory card				
Case type	Heavy Duty Metal Case				
Operation Panel	3 Keys, 2 LEDs and Liquid Crystal Display				
Weight	12 Kg	13 Kg	13 Kg		
Dimensions (W x D x H)	283 x 248 x 436 mm				
MTBF	Printer 100	0 Km, Head 5	0 Km		
Options and accessories	Autocutter 512K memory upgrade 256K flash memory card				

CLP 4081

CLP 4081R CLP 4081SR

Thermal transfer and direct thermal

Citizen Systems Europe GmbH Mettinger Strasse 11, D-73728 Esslingen **GERMANY**

Tel: +49 (0)711 3906 400 Fax: +49 (0)711 3906 405

Technical Specification

Technology

Citizen Systems Europe UK 337 Bath Road, Slough Berkshire, SL1 5PR UNITED KINGDOM

Tel: +44(0)1628 607300 Fax:+44 (0)1628 667346 sales@citizen.co.uk http://www.citizen.co.uk

Dealer Stamp			
'			

Note: These specifications are subject to change without notice. 4081-1-0999 1200291