

IMAGETEAM™ 3800ESD Series *Hand Held Linear Imager for ESD Sensitive and Clean Room Applications*



Features

High Resolution - Reads very high density bar codes 3 mil. and larger.

Clean Room Ready - Cleaned and triple bagged for Class 100 environments.

Bright, Sharp and Focused Aiming Line - Easy to aim and scan codes in any lighting condition from darkness to full sunlight, tightly stacked bar code sheets, or small, high resolution labels.

Solid, Rugged Design - No moving parts inside and solid construction outside deliver years of reliable service in demanding work environments.

Powerful, Flexible Architecture - Connects and interfaces to all major PCs and commercial terminals easily and quickly with Windows®-based programming tools or bar code programming menus.

Increased Reading Distances - Easily covers the full range of hand held scanning uses in industrial scanning applications.

Real World Reading Performance - Accommodates printer induced bar space variation, faded labels, short quiet zones, low contrast codes, dot matrix printing, and multipart forms with higher resolution, better optics, and improved decoding algorithms.

5 Year Warranty

The IMAGETEAM™ 3800ESD is a high performance scanner designed for the stringent requirements of clean room assembly of sensitive electronic components. The IT3800ESD is constructed of conductive materials engineered to eliminate the build up of dangerous static charge on the scanner, and to quickly drain the charge from any other object with which it comes in contact. The IT3800ESD is assembled for use in a Class 100 clean room environment and is triple bagged for proper introduction into the end use environment.

Internal components of the IT3800ESD scanner are isolated from the conductive path formed by the case, output connector shield, and special shielded cable with drain wire. The scanner is rated for discharges up to 15 kV without damage.

Two models are available: the IT3800VHD/ESD which reads very high density bar codes, and the IT3800LR/ESD for more typical applications.

All materials used in the IT3800ESD are tested using the methods described in ASTM D257, Standard Test Methods for Conductance of Insulating Materials. The surface resistivity is rated at less than 10E5 ohms/square. Triboelectric residual charge is measured with a non contact Electrostatic Field Meter and is less than 5 volts on any surface.

To learn how the IT3800ESD can work for you, contact us at any of the locations listed on the back or visit us at www.handheld.com.

IMAGETEAM™ 3800ESD Series Specifications

Performance

Illumination:	630 NM Visible Red LED
Receiving Device:	3648 element linear imager
Reading Distance:	1 in. (2.5 cm) to 8 in. (20.3 cm) on medium density codes
Reading Width:	5 in. (12.7 cm) code width at 7 in. (17.8 cm) distance
Resolution:	
VHD:	3 mil. at 3.5 in. (8.8 cm) distance
LR:	5 mil. at 3.5 in. (8.8 cm) distance
Skew Angle:	±55°
Pitch Angle:	±55°
Horizontal Velocity:	5 in. (12.7 cm) per second
Minimum Reflectance	
Difference:	30%
Scan Rate:	Programmable to 270 scans per second
Decode Rate:	270 decodes per second

Mechanical/Electrical

Dimensions	
Length:	5.3 in. (13.5 cm)
Height:	6 in. (15.2 cm)
Width:	3.1 in. (7.9 cm)
Weight:	6.3 oz. (179.2 g)
Housing:	Polycarbonate
Power Requirements:	5Vdc ± 10% at scanner
Current Draw:	<u>Scanning</u> <u>Standby</u>
@270 s/s	275mA 125mA
@67 s/s	150mA 125mA
Power Supply	
Noise Rejection:	Maximum 100mV peak to peak, 10 to 100 kHz

Environmental

Temperature	
Operating:	+32°F to +122°F (0°C to +50°C)
Storage:	-4°F to 140°F (-40°C to +60°C)
Humidity:	0 to 95%
Mechanical Shock:	Operational after 25 drops from 5 ft. (1.53 m) to concrete
Ambient Illumination:	0 - 70,000 lux
ESD Protection:	Functional after 15kV discharge
Vibration:	Withstands 5G peak from 20 to 300 Hz
Agency:	FCC Class B, CE EMC Class B, CE Low Voltage Directive, IEC60825-1 LED Safety: Class 1, UL, cUL listed, TÜV
MTBF:	per MIL-HDBK-217F Ground Benign exceeds 50,000 hours
Symbolologies:	Codabar, Code 3 of 9 including PARAF, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, Code 11, Code 93, Code 128, UPC, EAN/JAN, China Postal Code, RSS.
Interfaces:	All popular PCs and terminals via keyboard wedge, keyboard replacement/direct connect, Apple ADB, USB, TTL level serial wedge, TTL level RS-232, wand emulation mode, and includes (HHLC) non decoded laser compatible output.
Warranty:	Five year factory warranty.

Worldwide Offices

Offices Serving North America
Skaneateles Falls, NY
Tel: +1 315 685 8945
or, in North America: +1 800 582 4263
napresales@handheld.com
Charlotte, NC
Tel: +1 704 998 3998
or, in North America: +1 800 582 4263
napresales@handheld.com

Offices Serving Europe, Middle East, and Africa
Europe
Tel: +31 (0) 40 29 01 600
eupresales@handheld.com
United Kingdom
Tel: +44 (0) 1 925 240055
eupresales@handheld.com
Italy
Tel: +39 (0) 2 67 100752
eupresales@handheld.com

France
Tel: +33 (0) 1 41 158220
eupresales@handheld.com
Germany
Tel: +49 (0) 7 477 151377
eupresales@handheld.com
Spain
Tel: +34 93 228 78 68
eupresales@handheld.com

Offices Serving Asia and the Pacific Rim
Hong Kong
Tel: +852 2511 3050
appresales@handheld.com
Japan
Tel: +813 5770 6312
appresales@handheld.com

Offices Serving Latin America
Naples, Florida
Tel: +1 239 263 7600
lapresales@handheld.com
São Paulo
Tel: +55 11 5016 3454
lapresales@handheld.com
Rio De Janeiro
Tel: +55 21 2176 0250
lapresales@handheld.com

Web Site Address www.handheld.com

Hand Held Products, Inc., ("Hand Held Products") © 1999-2004. All rights reserved. Printed in the U.S.A.
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.