

# MX5



Standard or long-range 1D and 2D barcode scanner for maximum flexibility.

Ultra-rugged magnesium housing (IP67) for use in extreme environments.

Optional internal heater for operation in temperatures as low as -22° F (-30° C).

Supports LAN and WAN radios, enabling use in either the warehouse or the field.



## HANDHELD COMPUTERS

Color TFT reflective screen with touch screen for clear viewing both indoors and outdoors

Epoxy coated full alphanumeric keypad

'Built-in' customer support with LXE's ServicePASS<sup>SM</sup> program.

## LXE is RUGGED MOBILE COMPUTERS AND SECURE WIRELESS NETWORKS.

### Ultra-rugged industrial ergonomics

The MX5 is LXE's toughest Windows® based handheld, designed for extreme environments – from hot and humid ports to ice cold storage facilities and anything in between. The MX5 boasts the industry's leading water seal rating, and can easily withstand multiple drops from over six feet (2m).

### Highly reliable, industry-standard platform


The MX5's powerful Intel® XScale™ PXA255 400MHz processor and CE .NET 4.2 operating system ensure a mobile logistics computing solution designed to meet the demands of today's and tomorrow's mobile enterprise.



[www.lxe.com](http://www.lxe.com)

# MX5

## Technical Specifications



### Processing & Memory

- Intel® XScale® PXA255 400MHz CPU
- 128MB DRAM
- 256MB CF Flash

### Operating Systems & Emulations

- Windows® CE .NET 4.2

### Optional Software

- RFTerm® (TN5250, TN3270, VT220)
- AppLock® utility controls user application access & unwanted configuration changes
- API's for scanner, PCMCIA, serial, battery, power management, and version control
- SDK
- Personal JAVA 1.2 JVM

### Keyboard

- 52-key backlit keyboard
- Epoxy coated for resistance to abrasions
- 101 key support (IBM compatible)
- 3 emulation overlay options

### Display

- 240 x 320 / VGA TFT LCD
- (Indoor/Outdoor) Full sun light readable
- Reflective active color, front lit
- Diagonal viewing area 3.8" (9.7mm) 0.24 dot pitch
- Resistive touch screen with stylus
- Optional display heater

### Power Supply and Management

- 2800 mAh 7.4V Li-Ion battery pack with in-unit charging
- 8+ hour battery life (with typical usage)
- Backup battery
- Main battery low warning
- Active power management (configurable)

### Interfaces

- RS-232 (COM 1, COM 4)
- USB Client
- USB Host
- IrDA
- Ethernet 10/100Mb
- Speaker, Audio Microphone
- Headset Jack
- Power

### Expansion

- (1) PCMCIA v.2.1 slot Type II
- (1) compact flash slot Type II

### Radio Card Support

- 2.4GHz 802.11b
- Optimized internal antenna

### Enclosure

- Size: 10" x 3.9" x 2.1" (254mm x 100mm x 52mm)
- Weight: 34oz (985g) including radio, battery, scanner and handle

### Environmental

- Storage temperature range -22°F to 158°F (-30°C to 70°C)
- Operating temperature range -4°F to 122°F (-20°C to 50°C)
- Extended operation (with opt. heater) -22°F to 122°F (-30°C to 50°C)
- Humidity (operating) 5% to 90% RH non-condensing at 104°F (40°C)
- Drop specification (multiple drops to concrete) 6ft (2m).
- Dust and water protection enclosure rating exceeds IEC 60529 IP67
- Vibration testing Exceeds MIL STD 810F

### Bar Code

- Integrated 1D bar code scanners: Fuzzy logic (SR) Long range scanner (LR) Advanced long range (ALR) Integrated 2D (PDF-417) bar code scanner

### Bar Code Symbology

- Code 39, Interleaved 2 of 5
- UPC-A, UPC-E, Code 128
- Plessey, EAN-8 and EAN-13, Code 93 and Codabar and others not listed

### Approvals

- Emissions (EMI) FCC Part 15 Subpart B, Class B Industry Canada ICES-003 Class B EN 55022:1998, Class B
- Immunity (EMC)

EN 55024:1998

- Safety CSA C22.2 No. 60950, EN 60950, IEC 60950
- Laser safety CDRH:21 CFR 1040.10 and 1040.11, EN60825-1 AND IEC 825-1
- Radios separately approved to FCC part 15 subpart C Industry Canada RSS 102, RSS 139 and/or 210
- R&TTE Directive: ETS 300 323, ETS 300 826, EN 60950

### Accessories

- 6 unit battery charger
- Handle with scanner trigger
- AC & DC adapters
- Nylon hand strap
- Stylus
- Nylon holster
- Nylon case with shoulder strap
- Tethered stylus for cases and holsters
- Vehicle charging & communicating cradle
- Vehicle cradle power supplies
- Standard desktop charging & communication cradle
- Enhanced desktop charging & communication cradle with spare battery charging slot and ethernet support
- Flash memory cards
- USB interface cable
- RS-232 interface cable
- Ethernet interface cable
- Heater battery belt
- Battery belt charger and cables



### LXE Inc.

125 Technology Parkway – Norcross - Georgia 30092 – USA  
Tel. +1-770-447 4224 – Fax +1-770-447 4405  
E-mail info@lxe.com

### LXE International

Generaal de Wittelaan 19-14 – 2800 Mechelen – Belgium  
Tel. +32-15-29 28 20 – Fax +32-15-20 71 54  
E-mail RF4U@lxe.com

LXE Belgium +32-15 29 28 20 – info.be@lxe.com • LXE U.K. +44-1494 46 46 80 – info.uk@lxe.com • LXE Netherlands +31-346 21 70 70 – info.nl@lxe.com • LXE Italy +39-06 91 80 14 82 info.it@lxe.com • LXE France +33-1 41 47 99 99 – info.fr@lxe.com • LXE Germany +49-2461 690 450 – info.de@lxe.com • LXE Sweden +46-8 544 445 50 – info.se@lxe.com • LXE Australia +61-2 9666 57 51 – info.au@lxe.com • LXE Middle East +971-4 881 3070 – info.middle-east@lxe.com • LXE Singapore +65-6278 0593 – info.singapore@lxe.com

Published by LXE International. Specifications are subject to change without notice. All names, products and services mentioned are trademarks of their respective organisations.