

ST340T Rugged Tablet

Slim, Rugged, Multi-functional Wireless Computing



The Sumo Technologies ST340T Rugged Tablet features the integration of a brilliant 14" capacitive touch screen and high performance, energy-efficient Intel® 8th Generation Core™ i-quad-core processor within a slim, lightweight, durable package. With built-in smart card/CAC reader, Wi-Fi and Bluetooth as well as optional front camera, GNSS and mobile broadband, this tablet offers seamless information capture for instant transmission in the field and in the office. With its large, vivid display and optional graphic card, the ST340T Rugged Tablet supports a wider working area and detailed application interface along with higher image and video processing. The MIL-STD and IP ratings also make this tablet stand up to real world use for mission critical applications.

Features

- 14" Full-HD sunlight readable screen with capacitive touch
- Intel® 8th Generation Core™ i5/i7 quad-core processor
- NVIDIA GeForce® GTX 1050 graphic card option; ideal for defense, medical imaging, aerospace applications
- Built-in full-slot smart card/CAC reader
- Dual high-capacity, hot-swappable battery packs; up to 180W
- IP65-rated for water and dust resistance
- MIL-STD-810G for shock and vibration protection
- MIL-STD-461F for EMI and EMC Tolerance
- Foldable tabletop stand
- Optional front camera, GNSS and 4G LTE
- Optional dual pass through antennas for the docking cradle







Applications

- Government/ Military
- Manufacturing automation
- Law Enforcement
- Field Service/Utilities
- Transportation
- Construction
- Healthcare
- Education
- Aerospace Training

Specification

| System | | |
|--|---|--|
| СРИ | Intel® Core™ i5-8250U, Quad-Core, 1.6GHz (up to 3.4GHz) Intel® Core™ i7-8650U, Quad-Core, 1.9GHz (up to 4.2GHz) vPro support option | |
| RAM | 8GB, 16GB or 32GB | |
| Storage | 128GB to 1TB Flash | |
| Operating System | Microsoft® Windows® 10 IoT Enterprise, 64bit | |
| Display | 14" LED-backlight screen with capacitive touch, sunlight readable | |
| Display Resolution | 1920 x 1080 | |
| Control Switch and Buttons | 1 power button, 2 programmable buttons | |
| Indicator | 1 power/ battery status LED | |
| Microphone | Built-in microphone with DSP for real-time video | |
| Speaker | Built-in speaker | |
| Network Interface | | |
| WLAN | Wi-Fi 802.11ac, 2.4GHz/ 5GHz dual band | |
| Bluetooth | Bluetooth 4.0 LE | |
| I/O Ports | | |
| HDMI | 1 | |
| USB Port | USB 3.0 x 1 and USB 2.0 x 2 | |
| Headset Jack | 1 | |
| DC-in | 1 | |
| SD Slot | 1 micro SD card slot | |
| Ethernet | RJ45 connector for Ethernet x 1 | |
| Smart Card/CAC Reader | Full-slot, Reads ISO 7816 T=0, T=1; 1.8/3/5V smart card | |
| | | |
| Mechanical and Enviro | nmental | |
| Mechanical and Enviro | Input: 100 – 240V AC; Output: 19V DC, 6.31A | |
| | | |
| AC/DC Adapter | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 | |
| AC/DC Adapter Battery Packs | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-461F | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-461F IP65 | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-461F IP65 FCC Class B, CE, RoHS compliant Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810G | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance Regulatory | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-461F IP65 FCC Class B, CE, RoHS compliant Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety and optimal functionality and performance, the recommended | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance Regulatory | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-461F IP65 FCC Class B, CE, RoHS compliant Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F) | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance Regulatory Temperature | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-810G MIL-STD-461F IP65 FCC Class B, CE, RoHS compliant Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F) Storage: -55°C to 70°C (-67°F to 158°F) | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance Regulatory Temperature Humidity | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-810G MIL-STD-461F IP65 FCC Class B, CE, RoHS compliant Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F) Storage: -55°C to 70°C (-67°F to 158°F) | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance Regulatory Temperature Humidity Major Options | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-461F IP65 FCC Class B, CE, RoHS compliant Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F) Storage: -55°C to 70°C (-67°F to 158°F) 0% – 90% non-condensing | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance Regulatory Temperature Humidity Major Options Graphic Card | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-461F IP65 FCC Class B, CE, RoHS compliant Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F) Storage: -55°C to 70°C (-67°F to 158°F) 0% – 90% non-condensing Integrated graphic card, NVIDIA GeForce® GTX 1050 with 4GB VRAM 2 megapixel Full-HD front camera U-blox M8 GNSS module with concurrent reception of GPS and | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance Regulatory Temperature Humidity Major Options Graphic Card Camera | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-461F IP65 FCC Class B, CE, RoHS compliant Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F) Storage: -55°C to 70°C (-67°F to 158°F) 0% – 90% non-condensing Integrated graphic card, NVIDIA GeForce® GTX 1050 with 4GB VRAM 2 megapixel Full-HD front camera | |
| AC/DC Adapter Battery Packs Enclosure Dimensions (H x W x D) Weight Vibration and Shock Resistance EMI and EMC Tolerance Water and Dust Resistance Regulatory Temperature Humidity Major Options Graphic Card Camera GNSS Module | Input: 100 – 240V AC; Output: 19V DC, 6.31A Hot swappable battery, 11.4V, 5400mAh x 2 Hot swappable battery, 11.4V, 8000mAh x 2 (optional) ABS + PC plastics and magnesium-aluminum alloy 13.8 x 9.6 x 1.16 in/ 351mm x 244mm x 29.5mm 4.3 lbs/ 1.95kg MIL-STD-810G MIL-STD-810G MIL-STD-461F IP65 FCC Class B, CE, RoHS compliant Operation*: -20°C to 60°C (-4°F to 140°F); tested under MIL-STD-810G method 501.6, Procedure II, and method 502.6, Procedure II * For battery safety and optimal functionality and performance, the recommended usage temperature range is from -10°C to 45°C (14°F to 113°F) Storage: -55°C to 70°C (-67°F to 158°F) 0% – 90% non-condensing Integrated graphic card, NVIDIA GeForce® GTX 1050 with 4GB VRAM 2 megapixel Full-HD front camera U-blox M8 GNSS module with concurrent reception of GPS and GLONASS; industry leading -167dBm navigation sensitivity | |

Accessories

The ST340T tablet has customized accessories to meet numerous deployment needs.

| Digital Pen | | |
|-------------|--|----|
| Pen Tip | Diameter: 0.059 in/ 1.5mm, replaceable | |
| Buttons | 2 side buttons (right-click and eraser) | |
| Battery | 1 AAAA, replaceable | |
| Color | Black | |
| Dimensions | Length: 5.5 in/ 140 mm (including pen tip) Diameter: 0.38 in/ 9.7 mm | |
| Weight | 0.055 lbs/ 25 g | W. |

Docking Keyboard

With ports for Power, HDMI and USB; designed to connect to the Sumo tablet, instantly pairs, ideal for 2-in-1 applications.



Vehicle Mount Cradle

Supports ST340T and the Detachable Keyboard. The Cradle offers a lockable mechanism as well as USB, LAN, COM ports, a DC-in jack, and dual antenna connectors.



Battery Charging Kits





High Capacity Battery Pack





Sumo Technologies Ltd Manor Chambers, Marygate, York, YO30 7BH,

United Kingdom

Phone: +44 (0) 1904 670670 Fax:+44 (0) 1904 670570 info@sumohealthcare.com www.sumohealthcare.com