

POCKETABLE COMPUTERS

Rugged Mobility, Efficient Data Management and the Power of Palm™

The SPT 1800 Series of pen-notepad computers offers the most advanced Palm Powered™ solution for your work force. This family of rugged mobile computers combines integrated scanning, sophisticated wireless connectivity and powerful processing capability with the Palm OS® platform. With 1-D bar code data capture and wireless local area network (WLAN) or wireless wide area network (WWAN) communications, the SPT 1800 Series is a powerful productivity-enhancing tool, serving the multiple needs of today's growing mobile workforce.

Tackle Tough Environments

Tough enough for use in manufacturing and industrial environments, the SPT 1800 Series enables the Palm OS to perform practically anywhere. The rugged SPT 18XX housing is sealed to IP54 standards for protection against rain and dust, and withstands 4 ft./1.2 m drops to concrete.

Symbol's state-of-the-art scan engine with bright, easy to see scan line, delivers premium scanning performance under virtually any lighting condition—even sunlight or bright artificial light. A high-contrast, anti-reflective liquid crystal display makes data easy to read in low lighting or outdoor conditions.

Integrated WLAN or WWAN communication extends the reach of IT resources, enabling real-time information flow between the point of activity and your remote host system, making your business truly mobile.

Empower Your Work Force

The combination of rugged durability, integrated bar code scanning and wireless communication enables users in a host of industries to capture, compute and communicate data anytime, anywhere.

As shipments are unloaded, warehouse management can easily record new inventory levels to networked host systems. Service professionals in hospitality can offer curbside check-in at hotels, and hospital physicians and caregivers can have the latest patient data at hand.

Law enforcement officers can scan vehicle registration or drivers' licenses to gather information immediately, and wireless WAN communication enables them to send and receive information from the point of activity. In retail, when coupled with a magnetic stripe reader and portable printer, the SPT 1800 becomes a portable point-of-sale device, and, for scan-intensive tasks, an attachable handle converts the SPT 1800 into an ergonomic pistol grip design.



Features	Benefits
Spectrum24® Wireless LAN connectivity option	Enables full mobility with real-time data transmission to and from network information systems
Wireless WAN connectivity	Extends access to information beyond the enterprise
Supports Symbol's AirBEAM® suite of mobility management tools	Maximizes the availability, security and effectiveness of your wireless network investment
Kerberos security—industry standard authentication, key distribution and encryption	Advanced security with fast roaming for mobile data applications
Rugged housing meets IP54 standards	Withstands typical workday usage and tough industrial environments
8 or 16 MB of RAM and 4 MB of ROM	Accommodates application needs and memory demands
High-contrast liquid crystal display with enhanced backlight	Offers increased visibility for user comfort and acceptance
Rechargeable Lithium Ion battery plus a 1-hour Ni-MH backup battery	Long battery life enables full workday capacity plus extended backup ensures against data loss*
Supports single-slot serial and modem cradles/multi-slot serial and Ethernet cradles	Flexible host communications conveniently support various network environments

* Actual battery life may vary under different usage conditions

Mobile Solutions

Deployment of the SPT 1800 can help increase efficiency and productivity in your business, and a complete line of accessories and peripherals are available to create a total mobile solution. To learn more about the SPT 1800 Series or any of our innovative products, contact us at any of the locations listed on the back panel or visit us at www.symbol.com/palm

SPT 1800 Specification Highlights

Physical Characteristics

Dimensions:	1 in. H x 3 5/8 in. W x 7 in. L 25.4 mm H x 92 mm W x 177.8 mm L
Weight (including battery):	Batch version: 10.6 oz/300 gm; Wireless version: 12.2 oz./346 gm
Battery:	3.7 V, 1550 mAh rechargeable Lithium-Ion
Drop Specification:	4 ft./1.2 m to concrete
Environmental Sealing:	IP54 (windblown dust and rain)
Display:	High contrast, anti-reflective 160 x 160 monochrome LCD display
Operating Temperature:	-4° to 122°F/-20° to 50°C
Storage Temperature:	-13° to 122°F/-25° to 50°C
Humidity:	5% to 90% RH noncondensing
Electrostatic Discharge (ESD):	8kVdc air, 4kVdc contact

Performance Characteristics

CPU:	DragonBall VZ – 33 MHz
Operating System:	Palm OS® 4.X
Memory:	8 MB RAM / 4 MB ROM 16 MB RAM / 4MB ROM (Batch version only)
Application Development:	AppForge, CodeWarrior, MCL, GCC, PenRight! and SatelliteForms
Flash Tools:	ImagePro
Communications:	IrDA 1.0
Decode Capability:	Bookland EAN, Codabar, Code 128, Code 39, Code 93, Coupon Code, Discrete 2 of 5, EAN-13, EAN-8, Interleaved 2 of 5, ISBT128, MSI Plessey, Tri-optic Code 39, UCC/EAN 128, UPC/EAN Supplementals, UPC-A, UPC-E, UPC-E1

Wireless Local Area Network Characteristics

Wireless Local Area Network:	Symbol Spectrum24® IEEE 802.11 airwaves standard compliant / IEEE 802.11b
Radio Transmission Technique:	Frequency Hopping / Direct Sequence
Data Rate:	2 Mbps / 11 Mbps
Antenna:	Internal
Range:	Open space: up to 1000 ft./303 m Typical: 180 to 250 ft./54 to 76 m
Output Power:	500mW U.S.; 100 mW International
Frequency Range:	Country dependent, typically 2.4 to 2.5 GHz

Wireless Wide Area Network Characteristics

Network:	CDPD - 900 MHz
Output Power:	CDPD 600MW
Data Range:	CDPD up to 19.2 Kbps
Antenna:	External
Frequency Range:	CDPD 824-894 MHz

Peripherals and Accessories

Cradles:	Vehicle, modem, single/four-slot serial, four-slot charge only and four-slot Ethernet
Communication and Charging Cradles:	Serial/charging in terminal battery
Trigger Handle:	Via serial connection, attaches and converts SPT 18XX into a gun style device for scan-intensive applications
Magnetic Stripe Reader (MSR):	Serial connection for MSR readability
4-Slot Universal Battery Charger (UBC):	Recharges multiple batteries; battery adapter: used with Symbol's Universal Battery Charger

Printer Cables

O'Neil:	CBL-PT00100-ON1, CBL-PT00100-ON2
Paxar/Monarch:	CBL-1700-100-MON1, CBL-1700-100-MON2
Zebra/Comtec:	CBL-1700-100-CTC, CBL-1700-100-ELT

Regulatory

Electrical Safety:	Certified to UL 1950, CSA C22.2 No. 950; EN60950:1992/IEC950
EMI/RFI:	FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Australian SMA
Laser Safety:	CDRH Class II, IEC Class II
Hazardous Certified:	Certified to UL 913 and CAN/CSA C22.2 no. 157 for use in Class I, Division 2, Groups A, B,C,D SPT1800-TRG80400 SPT1846-TKG804U5



Specifications are subject to change without notice. Symbol®, Spectrum24® and AirBEAM® are the registered trademarks of Symbol Technologies, Inc. All other trademarks and service marks are proprietary to their respective owners.

For system, product or services availability and specific information within your country, please contact your local Symbol Technologies office or Business Partner.



Corporate Headquarters
Symbol Technologies, Inc.
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234/+1.631.738.2400
 FAX: +1.631.738.5990

For North America, Latin America and Canada
Symbol Technologies
 The Americas
 One Symbol Plaza
 Holtsville, NY 11742-1300
 TEL: +1.800.722.6234/+1.631.738.2400
 FAX: +1.631.738.5990

For Asia Pacific Area
Symbol Technologies Asia, Inc.
 (Singapore Branch)
 Asia Pacific Division
 230 Victoria Street #05-07/09
 Bugis Junction Office Tower
 Singapore 188024
 TEL: +65.6796.9600
 FAX: +65.6337.6488

Symbol Website
 For a complete list of Symbol subsidiaries and business partners worldwide contact us at:
www.symbol.com
E-mail
info@symbol.com

For Europe, Middle East and Africa
Symbol Technologies
 EMEA Division
 Symbol Place, Winnersh Triangle
 Berkshire, England RG41 5TP
 TEL: +44.118.9457000
 FAX: +44.118.9457500



Part No. SPT1800 Printed in USA 12/02 ©2002 Symbol Technologies, Inc.
 Symbol is an ISO 9001 and ISO 9002 UKAS, RVC, and RAB Registered company, as scope definitions apply.

