



T30 Label Rewinder

The Rewinder Everyone Can Use

The T30 rewinder has an idler arm that can be positioned to rewind labels from either side of the printer.

Depending on the user's requirements, the rewinder can rewind "inside or outside" label rolls.



Modular core adaptor fits 1", 1.5" & 3" core sizes



Colored LED indicator provides rewinder operation status



Rewinding direction switch to rewind "inside or outside" label rolls



Easy assembly lock module for quickly and firmly label roll holding



Model		T30
Paper width		8,46"
Rewind Speed		Auto mode: 12 IPS (max) Fixed mode: Coreless 5.4 IPS, 1 inch Roll 6.3 IPS
Label Roll		6,3" (Max.)
Core Roll		Coreless, 1" (25.2~25.6mm), 1.5"x2 (37.4~38.0mm & 40~40.6mm), 3" (76~76.6mm)
Label Roll Weight		5,5 Kg (12lb)
Rewinding		Label Inside / Outside
Switches		Rewind
Motor		Hybrid Motor
Power		100~240VAC 24W, 24V Adapter
Environment	Operation Temp	41°F to 104°F(5°C to 40°C)
	Storage Temp	-4°F to 122°F(-20°C to 60°C)
Humidity		10-85% (non-condensing RH)
Size (H*W*D)		303mm*230mm*349mm
Agency Approvals		CE, FCC Class A
Weight		5,5 Kg (12lb)

^{*} Specifications are subject to change without notice. All company and/or product names are trademarks and/or registered trademarks of their respective owners.

Godex Americas Telephone: +886 2 2225 8580 Telephone: +1 805 987 5100 Telephone: +86 21 56651313 Telephone: +49 2195 59599 0

Contact us: infoGT@godexintl.com Contact us: infoGC@godexintl.com Contact us: infoGC@godexintl.com

Godex China

Godex Europe