

VX8 Kärv

PREPARED FOR BATTLE.
DESIGNED FOR COMMERCE.



Centuries ago, the kärv was an agile seafaring vessel used in both battle and merchant missions. Today, the LXE Kärv is a compact, rugged, and wirelessly-enabled mobile PC designed to be every bit as versatile as its namesake.

The Kärv is designed for enterprises that need full Microsoft® Windows computing power in a mobile environment to optimize application and network management compatibility, and is flexible enough to run multiple advanced applications, with either Windows XP Professional MUI or Windows Embedded Standard. Radio communications are delivered on the move with optional Bluetooth, WLAN or WWAN radio configurations. And it's all packaged in an IP 65-rated magnesium enclosure that's built to thrive in the toughest environment — yours.

To see how the agile and versatile Kärv fits into your operation, or to check out the entire Trux family of vehicle mount computers, please visit lxe.com/karv.

 OUTDOOR DISPLAY

 -22° F

 IP 65



AGILE

Compact size (11" x 9" x 3") and multiple mount options ideal for tight spaces

POWERFUL

High-strength magnesium housing protects an equally powerful Intel® Core 2 Duo or Atom Processor

VERSATILE

Ambient-light sensor and available energy-efficient LED backlit display ready for any environment

VX8 Kärv

TECHNICAL SPECIFICATIONS



PLATFORM

Processing & Memory



Intel® Core 2 Duo 1.5GHz, RAM: 1GB DDR standard (2GB optional)



Intel® Atom 1.6GHz, RAM: 1GB DDR standard (2GB optional)

- Intel® Mobile Pentium 1.4GHz: 512MB DDR standard (1GB optional)
- Intel® Mobile Celeron 1.0GHz: 512MB DDR standard (1GB optional)
- Intel® Mobile Celeron 600MHz: 512MB DDR standard (1GB optional)

System

- Windows® XP Professional MUI
- Windows® Embedded Standard (WES 2009)
- Windows® XP Embedded (XPE)



Windows® 7 Ready

Graphics Card

- Intel® Extreme Graphics 2, 32 MB RAM

Display & Touch Screen

- Indoor 10.4" (264mm) TFT flat panel, SVGA (800x600)

LED Backlit*

- Maximum brightness: 400 cd/m²
- Contrast ratio 700:1

CCFL Backlit

- Maximum brightness: 400 cd/m²
- Contrast ratio 500:1

*Available w/ Intel® Atom and Core 2 Duo only

- Light sensor for automatic display adjustment
- Touch screen options: Standard, Hardened, Defroster

Hard Drives

- 60 GB 2.5" Hard Drive Automotive
- 16 GB Solid State Drive
- 8 GB Compact Flash
- 4 GB Compact Flash
- 2 GB Compact Flash (XPE/WES Only)

Power Supply & UPS

- External power supply 10-150VDC
- Integrated Li-ION battery backup
- Integrated backup battery charger

Enclosure

- High strength magnesium housing
- Weight: 7.7 lbs. (2.9 kg)
- Dimensions: 11" x 9" x 3" (279mm x 229mm x 77mm)
- Shock-absorbing mounting system

CONNECTIVITY

System Software

- VMT Manager (Config. Utility)
- Citrix® Client
- Windows® Terminal Services

Optional Software

- RFTerm® (Windows Terminal Emulations VT220, TN5250, TN3270)
- FreeFloat® Terminal Emulator (VT220, TN5250, TN3270)
- Barcode Wedge
- On-screen soft keyboard

Interfaces

- 2 PS/2 ports (1 keyboard, 1 mouse) w/strain relief
- 2 Serial ports (COM1) and (COM2) support 5V or 12V to external units
- 2 USB 2.0 ports (w/ strain relief)
- 1 Multi-purpose connector (Serial + USB)
- 1 RJ-45 ethernet 10/100

- 1 Audio out (head set)
- 1 Mic in (microphone)
- 1 VGA connector
- Onboard speakers (front)
- 1 Internal USB 2.0
- 2 Mini-PCI
 - PC Card Adapter Option

Radio Support

- WLAN: 802.11 a/b/g
- WWAN GSM/GPRS Edge
 - HSDPA/HSUPA/UMTS/HCDMA
 - Multiband 850/900/1800/2100 MHz
 - Remote GSM/GPRS antenna included
- Bluetooth® 2.0+EDR
- WPA and WPA2 security
- Dual diversity external antennas
- Remote mount antenna kits available

ENVIRONMENTAL

Operating temperature:

-22 to +122°F (-30 to +50°C)

Storage temperature:

-4 to +122°F (-20 to +50°C)

Start-up temperature:

-4 to +122°F (-20 to +50°C)

- Dust and water protection enclosure rating compliant to IEC 60529 IP65

Approvals

- Temperature
 - Cold: IEC 60068-2-1, Test Aa
 - Dry heat: IEC 60068-2-2, Test Bc
 - Change of temperature: IEC 60068-2-14, Test Nb
- Moisture: According to IEC 60068-2-30, Test Db.
- Mechanical Vibration: According to IEC 60068-2-64, Test Fh
- Bump: According to IEC 60068-2-29, Test Eb
- Conformity: CE, FCC, and ETL

ACCESSORIES

- Multiple rugged keyboard options
- Fully isolated & protected external power supply
- Multiple RAM Mount mounting options

- Screen blanking box
- Data and adapter cables
- Bar code scanners (tethered & wireless)

Download accessory catalog at lxe.com



Copyright © 2010 LXE Inc. All rights reserved. Specifications are subject to change without notice. All names, products, and services mentioned are the trademarks or registered marks of their respective organizations.

DSKARV - 0210

LXE®

125 Technology Parkway
Norcross, GA 30092
1-800-664-4593
www.lxe.com