

SPP-A200

2-inch Thermal Mobile Printer



Field Service



Mobile POS / Retail



Deliveries



Customer Service Center



Ticketing

Flexible Payment Printing Solution



Optimised Mobile Printing

- Print speeds up to 80 mm/sec
- Direct connects via USB
- 1.0 m / 3.3 ft drop rate
- 31-hour stand by time once fully charged
- Integrate 7.4 V Li-ion, 1,200 mAh battery



Unique & Easy to Use Design

- Efficient space utilization
- Improve convenience when carrying the device
- Simultaneously charge printer and 3rd party PED
- One touch cover open and easy paper loading



Premium mPOS Payment Solution

- 2.3 inch TTF color LCD
- Support major mobile wallets and scheme brands
- Bi-directional and triple track secure MSR
- Wireless and wired connectivity options including Bluetooth, WiFi, USB
- Approve all security and scheme certifications

SPP-A200

2-inch Thermal Mobile Printer

5x
No.1 RECEIPT
MOBILE
PRINTER
MANUFACTURER



Reported by
Chunichisha

Specifications

Printer Specifications

Print Method

Direct Thermal

Print Speed

Up to 80 mm/sec (Receipt)
12.5% pattern

Print Resolution

203 dpi

Print Width

Up to 48 mm

Sensor

Paper End

Media Characteristics

Media Type

Receipt

Media Width

58 mm

Media Roll Diameter

Up to 30 mm

Media Thickness

0.07 ± 0.005 mm

Supply Method

Easy Paper Loading

Physical Characteristics

Dimensions (WxLxD)

82.8 × 149 × 41 mm
(3.26 × 5.87 × 1.61inch)

Weight

Including battery: 240 g (0.53 lbs.)
Paper : 34 g (0.07 lbs.)

Battery

7.4 V Li-ion, 1,200 mAh,
Rechargeable Charging time: Up to 2.5 hrs

Performance Characteristics

Memory

8 MB SDRAM, 4 MB Flash

Interface Options

Standard: USB V2.0 FS

Environment Characteristics

Temperature

Operating: -15 ~ 50°C (5 ~ 122°F)
Storage: -30 ~ 70°C (-22 ~ 158°F)

Humidity

Operating: 10~80% RH

Drop Rate

1.0 m (3.3 ft.)

Software

Emulation

BXL / POS

Fonts / Graphics / Symbologies

Fonts

Font A: 12 x 24 Font B: 9 x 17 Font C: 9 x 24
KOR, CHN, JPN: 24 x 24

Characters Per Line

Font A: 32 Font B, C: 42
KOR, CHN, JPN: 16

Character Sets

Alphanumeric: 95
Expanded Graphics: 128 x 33 page
International: 32

Graphics

Supporting user-defined fonts, graphics,
formats, layouts, and logos

Barcode Symbologies

1D: Codabar, Code 39, Code 93, Code 128,
EAN-8, EAN-13, ITF, UPC-A, UPC-E
2D: Aztec, Data Matrix, MaxiCode, PDF417,
QR code

Accessories

Standard

Battery Pack, SMPS, Power Cord, Paper

Optional

Single Battery Cradle, Quad Battery Charger,
Wall Mount (for Quad Battery Charger),
Cleaning Pen



BR-SPP-A200-EN-FEB19-V1

Copyright © BIXOLON Co., Ltd. All rights reserved. Features and specifications are subject to change without prior notice.

BIXOLON®

BIXOLON Co.,Ltd.
+82 (0) 31 218 5500
sales@bixolon.com

BIXOLON America Inc.
+1 858 764 4580
sales@bixolonusa.com

BIXOLON Europe GmbH
+49 211 68 78 54 0
sales@bixolon.de

www.Bixolon.com

