



## Label printers A<sup>+</sup> and X series

Made in Germany

# Contents

<b>Industrial label printers</b>	<b>3</b>
<b>Label printers A+ series - overview of types</b>	<b>4-5</b>
<b>Label printers with centered material guide</b>	<b>6-7</b>
<b>Label printers for double-sided printing</b>	<b>8-9</b>
<b>Label printers for two-color printing</b>	<b>10-11</b>
<b>Label printers - technical data</b>	<b>12-13</b>
<b>Accessories - overview</b>	<b>14</b>
<b>Accessories - special equipment, interfaces, connecting cables</b>	<b>15</b>
<b>Accessories - cutting labels, perforating labels, stacking labels</b>	<b>16</b>
<b>Accessories - rewinding labels, unwinding labels</b>	<b>17</b>
<b>Accessories - dispensing labels</b>	<b>18-19</b>
<b>Applicator A1000.</b>	<b>20</b>
<b>Accessories - applicator A1000.</b>	<b>21</b>
<b>Applicator A3200.</b>	<b>22</b>
<b>Accessories - mounting equipment</b>	<b>23</b>
<b>Label software cablabel S3</b>	<b>24</b>
<b>Integration</b>	<b>25</b>
<b>Stand-alone operation, easy maintenance</b>	<b>26</b>
<b>Service, training</b>	<b>27</b>
<b>Label printers - product range</b>	<b>28</b>
<b>Accessories - product range.</b>	<b>29-30</b>
<b>cab product range at a glance</b>	<b>31</b>

*All information on scopes of delivery, design and technical specifications correspond to the date of the printing. Subject to change.*

*For current data see website  
[www.cab.de/en/labelprinter](http://www.cab.de/en/labelprinter)*

# Industrial label printers



Professional industrial cab label printers are used in a wide variety of applications. Their development is first and foremost focused on simple and convenient operation coupled with high reliability.

Printing units and housings are made of high-quality materials and are perfectly matched in terms of shape and function. Extensive peripherals and software enable customized solutions – at any time.

Regardless of whether the A+ or X printer series is operated as a stand-alone solution, a PC application or in a network, it is always up to the mark. The high-speed processor ensures both fast job processing and immediate label output.

## Sample applications:

### PCB labels

If there is only little space available – smallest label size 4x4 mm



### Type plates

Pin sharp 600 dpi fonts, graphics and barcodes



### Cardboard box and pallet labels

Labels up to standard A4 format



# Label printers A+ series - overview of types



## The sleek one

For **small labels with high printing accuracy**

1.1	Label printer	A2+	
	Printable resolution dpi	300	600
	Print width up to mm	54.2	57
	Print speed up to mm/s	150	100



## The all-purpose one

Top-selling **industrial device with high printing accuracy**. Extensive range of accessories included.

1.2	Label printer	A4+		
	Printable resolution dpi	203	300	600
	Print width up to mm	104	105.6	105.6
	Print speed up to mm/s	250	250	100



## The wide one

Ideal for **Odette and UCC labels**

1.3	Label printer	A6+	
	Printable resolution dpi	203	300
	Print width up to mm	168	162.6
	Print speed up to mm/s	200	200



## The extra wide one

For **pallet and barrel labels**

1.4	Label printer	A8+
	Printable resolution dpi	300
	Print width up to mm	216
	Print speed up to mm/s	150



### Basic version

For printing on labels and continuous materials. The material is torn off at the jagged tear-off edge. Optionally, it may be cut or rewound externally.




### Dispensing version

For printing and dispensing labels. The label is removed from the liner during the printing process. It can be removed manually, by applicator or robot.



## Common details



***Pictured:  
Label printer A4+  
with dispensing function***

### **1 Wide graphic display**

White backlight for optimum readability.

### **2 Ribbon holder**

Three-part tightening axles enable a quick and easy exchange of ribbons.

### **3 Simple adjustment**

The print head is pressed down by two toggles. One is mounted to the left label margin, the other is pushed to the right label margin.

### **4 Peripheral connection**

All add-on modules are easy to connect. All peripheral devices are plugged in the printer using two pins and are fixed in place with a screw.

### **5 Solid metal chassis**

Die-cast aluminum. All components are mounted on it.

### **6 Roll holder**

Available for core diameters starting 38 mm (76 mm adapters for improved label winding are provided). The spring-mounted margin stop ensures constant tension during feeding, thus ensuring high printing accuracy.

### **7 Internal rewinder**

The rewinder with a three-part tightening axle ensures easy rewinding and removing of labels or liners with or without paper core.

### **8 Peel-off function**

The label is removed from its liner via peel-off plate. High printing and dispensing accuracy can be achieved via powered rewind assist and pinch rollers.

### **Compact cover**



The two-part cover made of impact-resistant ABS plastic folds up when opened.

### **1.11 Metal cover**



On request, label printers A4+ and A6+ are available with metal cover (standard with the A8+).

## Label printers with centered material guide



**All materials** that are wound on **rolls** or **reels** can be marked. Especially **very small labels** and **slim continuous materials** such as pressed tubes.

- No adjustment of print head for different widths of material
- Print rollers for narrow and slim materials
- Operation and control are compatible with the A+ series

1.5	Label printer		A4+M	
	Printable resolution	dpi	300	600
	Print width	up to mm	105.6	105.6
	Print speed	up to mm/s	125	100



**All materials** that are wound on **rolls** or **reels** can be marked. Particularly for **textile materials** there is a drive roller installed next to the print head. It enables the textile material to be separated from the ribbon and furthermore improves the accuracy and precision in a print.

- No adjustment of print head for different widths of material
- Print rollers for narrow and slim materials
- Operation and control are compatible with the A+ series

1.7	Label printer		A4+T	
	Printable resolution	dpi	300	600
	Print width	up to mm	105.6	105.6
	Print speed	up to mm/s	125	100

## Accessories



### Cutter

Used to cut paper labels, self-adhesive labels, cardboard, textile or synthetic materials as well as heat shrink tubes.


### Perforation cutter

Enables the perforation of the material for later manual separation.



### Stacker with cutter

Printed materials are cut and stacked. The print job is stopped as soon as the maximum stack height is reached. Even stiff or curved materials may be processed. We recommend to have your material tested at our facilities.




### Print rollers for small and thin materials

Outside the material width the print head rubs against the print rollers. By using small print rollers feeding errors and wear on print head and print roller due to rubbing are avoided. Three different standard widths are available from stock.

## Common details



**Pictured:**  
**Label printer A4+M**  
**with centered material guide**



**Pictured:**  
**Label printer A4+T**  
**with centered material guide**

### 1 Wide graphic display

White backlight for optimum readability.

### 2 No print head adjustment

The print head is pressed down by two toggles. Due to a centered material guide there is no need to do print head adjustments and settings.

### 3 Material guide

High printing accuracy as the material is located directly behind the print roller. Width adjustment with a single knob.

### 4 Separator (A4+T only)

Preferred application with continuous and textile materials as well as pressed tubes. The transfer tape may stick with the textile tape after the printing. With a drive roller, the material is separated from the ribbon. In addition, the accuracy of impression is improved.

### 5 Peripheral connection

Add-on modules such as cutter, perforation cutter and stacker are easy to connect.

### 6 Solid metal chassis

Die-cast aluminum. All components are mounted on it.

### 7 Antistatic brush

Particularly in case of plastic materials electrostatics is discharged after printing.

### 8 Ribbon holder

Simple, centered insertion of the ribbon with three-part tightening axles. Imprinted rule simplifies ribbon positioning.

### 9 Roll holder

Available for core diameters starting 38 mm (76 mm adapters for improved label winding are provided). The material is automatically centered. The spring-mounted margin stop ensures constant tension during feeding, thus ensuring high printing accuracy.

## Label printers for double-sided printing



It prints double-sided on **textile materials, cardboard labels, pressed tubes**, continuous or ready-for-use, as well as on **continuous sythetic, paper or cardboard materials**. A drive roller enables the materials to be separated from the ribbon and furthermore improves the accuracy and precision in a print.

- No adjustment of print head for different widths of material
- Print rollers for narrow and slim materials
- Operation and control are compatible with the A+ series

1.8	Label printer	XD4T
	Printable resolution dpi	300
	Print width up to mm	105.6
	Print speed up to mm/s	125

## Accessories



### Cutter

Used to cut paper labels, self-adhesive labels, cardboard, textile or synthetic materials as well as heat shrink tubes.


### Perforation cutter

Enables the perforation of the material for later manual separation.



### Stacker with cutter

Printed materials are cut and stacked. The print job is stopped as soon as the maximum stack height is reached. Even stiff or curved materials may be processed. We recommend to have your material tested at our facilities.




### Print rollers for small and thin materials

Outside the material width the printhead rubs against the print rollers. By using small print rollers feeding errors and wear on print head and print roller due to rubbing are avoided. Three different standard widths are available from stock.



# Details



***Pictured:  
Label printer XD4T  
for double-sided printing***

## **1 Wide graphic display**

White backlight for optimum readability.

## **2 No print head adjustment**

The print head is pressed down by two toggles. Due to a centered material guide there is no need to do print head adjustments and settings.

## **3 Material guide**

High printing accuracy as the material positioning is located directly behind the print roller. Width adjustment with a single knob. The additional drive roller enables the material to be separated from the ribbon.

## **4 Separator**

Preferred application with continuous and textile materials as well as pressed tubes. The transfer tape may stick with the textile tape after the printing. With a drive roller, the material is separated from the ribbon. In addition, the accuracy of impression is improved.

## **5 Peripheral connection**

Add-on modules such as cutter, perforation cutter and stacker are easy to connect.

## **6 Solid metal chassis**

Die-cast aluminum. All components are mounted on it.

## **7 Antistatic brush**

Particularly in case of plastic materials electrostatics is discharged after printing.

## **8 Ribbon holder**

Simple, centered insertion of the ribbon with three-part tightening axles. Imprinted rule simplifies ribbon positioning.

## **9 Roll holder**

Available for core diameters starting 38 mm (76 mm adapters for improved label winding are provided). The material is automatically centered. The spring-mounted margin stop ensures constant tension during feeding, thus ensuring high printing accuracy.

# Label printers for two-color printing



Two in-line arranged thermal transfer print units for **simultaneous two-color printing** in one label. With ribbon saver at one print unit.

- The XC series meets the conditions for the classification and labeling inventory according to GHS.
- For large label rolls up to 300 mm diameter
- The two print units including ribbon holder, operation panel and electronics are adopted from the proven A+ series.

1.9	Label printer	XC4
	Printable resolution	300 dpi
	Print width	up to 105.6 mm
	Print speed	up to 125 mm/s



1.10	Label printer	XC6
	Printable resolution	300 dpi
	Print width	up to 162.6 mm
	Print speed	up to 125 mm/s

We are glad to assist you in the selection of proper ribbons.

## Accessories




**Cutter**  
Used to cut paper labels, self-adhesive labels, cardboard, textile or synthetic materials as well as heat shrink tubes.

**Perforation cutter**  
For XC4 printers only. Enables the perforation of the material for later manual separation.



**Stacker with cutter**  
For XC4 printers only. Printed materials are cut and stacked. The print job is stopped as soon as the maximum stack height is reached. Even stiff or curved materials may be processed. We recommend to have your material tested at our facilities.

## Common details



### **1 Wide graphic display**

White backlight for optimum readability.

### **2 Ribbon holder**

Simple, centered insertion of the ribbon with three-part tightening axles.

### **3 Simple adjustment**

The print head is pressed down by toggles. One is mounted to the left label margin, the other is pushed to the right label margin.

### **4 Antistatic brush**

Particularly in case of plastic materials electrostatics is discharged after printing.

### **5 Peripheral connection**

All add-on modules are easy to connect. All peripheral devices are plugged in the printer using two pins and are fixed in place with a screw.

### **6 Solid metal chassis**

Die-cast aluminum. All components are mounted on it.

### **7 Roll holder**

For labels up to 300 mm diameter. Swing lever and integrated brake make sure that the labels are unwound with constant tension.

### **8 Ribbon saver for print head 1**

The ribbon saver is used for labels to be partially printed. The print head is lifted within the unprinted area and the ribbon stopped during label feeding.

### **9 Fanfold guide**

Fanfolded labels are positioned behind the print unit. Guide and additional brake ensure reliable feeding to the print unit.

# Label printers - technical data

■ Standard □ Optionally

■ Standard	□ Optionally		1.1		1.2		1.3		1.4		1.5		1.7		1.8		1.9		1.10					
Label printer			A2+		A4+		A6+		A8+		A4+M		A4+T		XD4T		XC4		XC6					
Print head																								
Printing method			thermal transfer		■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■				
			thermal direct		■	–	■	■	–	■	■	■	■	–	–	–	–	–	–	–	–			
Printable resolution			dpi		300	600	203	300	600	203	300	300	300	600	300	600	300	300	300	300				
Print speed			up to mm/s		150	100	250	250	100	200	200	150	125	100	125	100	125	125	125	125				
Print width			up to mm		54.2	57	104	105.6	105.6	168	162.6	216	105.6	105.6	105.6	105.6	105.6	105.6	162.6					
Material																								
										Paper, cardboard, textile, plastics														
Labels or continuous materials on rolls or fanfold			■		■		■		■		■		■		■		□ <sup>1)</sup>		□ <sup>1)</sup>					
Labels on reel			–		–		–		–		■		■		■		–		–					
Material thickness mm/weight g/m <sup>2</sup>			0.05-0.8/60-300																		0.05-0.2/60-180			
Width labels <sup>2)</sup>			mm		4-63		20-116		46-176		46-220		4-106		4-106		10-110		20-116		46-176			
liner			mm		24-67		24-120		50-180		50-235		10-110		10-110		10-110		24-120		50-180			
continuous material			mm		24-67		24-120		50-180		50-235		4-110		4-110		4-110		–		–			
contin. heat shrink tube			mm		10-67		25-85		–		–		4-85		4-85		4-85		–		–			
Label without back-feed			from mm		4		4		6		10		5		5		20		20		20			
height <sup>2)</sup> when dispensing			from mm		12		12		25		–		–		–		–		–		–			
			up to mm		5,000		2,000		5,000		4,000		1,000		4,000		3,000		2,000		1,500			
Media roll			outer diam.		up to mm		205		205		205		205		205		205		300		300		300	
			core diameter		mm		38-100		38-100		38-100		38-100		38-100		38-100		38-100		76		76	
winding			Outer or inner																					
Ribbon																								
Ink side			Outer or inner																					
Roll diameter			up to mm		80		80		80		72		80		80		72		72		72			
Core diameter			mm		25		25		25		25		25		25		25		25		25			
Variable length			up to m		500		500		500		360		500		500		360		360		360			
Width <sup>3)</sup>			up to mm		57		114		165		220		114		114		114		114		165			
Internal rewinder (only with peel-off devices)																								
Outer diameter			up to mm		142		142		142		–		–		–		–		–		–			
Core diameter			mm		38.1		38.1		38.1		–		–		–		–		–		–			
Label winding			Outer only																					
Dimensions and weights																								
Height			mm		274		274		274		274		274		274		395		395		395			
Depth			mm		446		446		446		446		446		446		554		554		554			
Width			mm		190		242		302		352		242		242		248		248		358			
Weight			kg		8.5		9		13		15		9		9		21		22		24			
Label sensor																								
Gap sensor			For leading edge or punch marks and end of material																					
Reflective sensor from bottom/opt. top			For print marks																					
Distance to locating edge			mm		5-26		5-53		5-53		5-53		–		–		–		5-53		5-53			
center to the left			mm		–		–		–		–		0-53		0-53		0-53		–		–			
Electronics																								
Processor 32 bit clock rate			MHz		266																			
Main storage (RAM)			MB		64																			
IFFS printer memory			MB Flash		8																			
Plug-in CompactFlash Type I			■																					
WLAN card			■																					
Battery buffer for real-time clock			■																					
Acoustic error signal			■																					
Interfaces																								
Centronics according to IEEE 1284			□																					
RS232 C			■																					
USB 2.0 hi-speed slave for PC			■																					
Ethernet 10/100 Base T, LPD-, RawIP-, FTP-Printing, DHCP, HTTP, SMTP, SNMP, TIME, Zeroconf, mDNS, SOAP			■																					
RS422/RS485			□																					
Peripheral connection			■																					
WLAN 802.11b/g, WEP/WPA-PSK (TKIP)			□																					
2xUSB hosts for external operation panel, keyboard, scanner, service key, USB stick			■																					
Operating data																								
Power supply			100-240 VAC ~ 50/60 Hz, PFC																					
Power consumption			W		100-300 depending on type of printer																			
Temperature/humidity operation			5-40 °C/10-85 % not condensing																					
storage			0-60 °C/20-80 % not condensing																					
transport			–25-60 °C/20-80 % not condensing																					
Approvals			CE, FCC class A, CB, CCC, UL																					

<sup>1)</sup> Continuous materials on rolls only after being tested. <sup>2)</sup> Limitations may apply to small labels, thin materials or strong adhesives. These applications need to be tested and approved.

<sup>3)</sup> Ribbon according to label width in order to avoid folding.



Operation panel		
Buttons/LED displays	Pause, feed, cancel, menu, enter, 4 x cursor	
LCD graphic display	Width 60 mm, height 40 mm, 4 lines text, approx. 20 characters per line	
Settings		
	Digital or analog clock	Time
	System settings	Date
	Print parameters	Interfaces
	Language settings	Security
On display		
	Data reception	Clock
	WLAN field intensity	Date sheet
	Ethernet status	abc Debug
	Used memory	Input buffer
	Temperature print head	Remaining ribbon
	Memory card access	
Monitoring		
Stop print job	When end of ribbon When end of labels When print head open When not reached final position of cutter	
Testing functions		
System diagnosis	When switched on, including print head testing	
Short status, status print	Fonts list, devices list, WLAN status, label profile, test grid, monitor mode, PPP status	
Status reports	Printout on device settings, e.g. print length counter, runtime counter, etc. Request of status via software command, status messages on display, e.g. network error - no link, barcode error, etc.	
Fonts		
Font types	5 bitmap fonts, incl. OCR-A, OCR-B and 3 vector fonts Swiss 721, Swiss 721 bold and Monospace 821 internally available, TrueType fonts loadable. Optionally: Chinese (simplified), Thai	
Character sets	Windows 1250 to 1257, DOS 437, 737, 775, 850, 852, 857, 862, 864, 866, 869, EBC DIC 500, ISO 8859-1 to -10 and -13 to -16, WinOEM 720, UTF-8, Macintosh Roman, DEC MCS, KOI8-R. All Western and Eastern European characters, Latin, Cyrillic, Greek, Hebrew and Arabic are supported. Optionally: Chinese (simplified), Thai	
Bitmap fonts	Size of width and height 1-3 mm Zoom factors 2-10 Orientation 0°, 90°, 180°, 270°	
Vector/TrueType fonts	Size of width and height 0.9-128 mm Variable zoom, orientation 360° in steps of 1°	
Font formats	Bold, italic, underlined, outline, inverse - depending on font types	
Font width	Variable	

Graphics			
Graphic elements	Lines, arrows, boxes, circles, ellipses, filled and filled with fading		
Graphic formats	PCX, IMG, BMP, TIF, MAC, GIF, PNG		
Barcodes			
Linear barcodes	Code 39, Code 93 Code 39 Full ASCII Code 128 A, B, C EAN 8, 13 EAN/UCC 128 EAN/UPC Appendix 2 EAN/UPC Appendix 5 FIM HIBC	Interleaved 2/5 Ident and lead code of Deutsche Post AG Codabar JAN 8, 13 MSI Plessey Postnet RSS 14 UPC A, E, E0	
2D codes	Aztec, Codablock F, Data Matrix, PDF 417, Micro PDF 417, UPS Maxicode, QR code, RSS 14 truncated, limited, stacked and stacked omnidirectional, EAN Datamatrix, GS1 Data Bar  All codes are variable in height, module width and ratio. Orientation 0°, 90°, 180°, 270°. Optionally with check digit, printed characters and start/stop code depending on type of code		
Software			
Programming	J-Script direct programming abc Basic Compiler Database Connector	■ ■ ■	
Monitoring/ administration	Printer monitoring Administration Network Manager	■ ■	
Label software	cablabel S3 Lite cablabel S3 Viewer cablabel S3 Pro cablabel S3 Print	■ ■ □ □	
Windows drivers certified	32/64 bit for Windows Vista Windows 7 Windows 8 Windows 8.1 Windows 10	Server 2003 Server 2008 Server 2008 R2 Server 2012 Server 2012 R2 ■	
Mac drivers*	OS X printer drivers starting version 10.6		■
Linux drivers*	32/64 bit starting CUPS 1.2		■
Stand-alone operation			■


















\*only with A+ series

# Accessories - overview

● Typical    ○ Possible    ■ Standard    □ Optionally

			1.1	1.2	1.3	1.4	1.5	1.7	1.8	1.9	1.10
Extra equipment			A2+	A4+	A6+	A8+	A4+M	A4+T	XD4T	XC4	XC6
2.1	Metal cover	●	-	□	□	■	□	-	■	■	■
2.2	Print rollers DR4-M25, -M50, -M80	●	-	-	-	-	□	□	□	-	-
2.3	Antistatic brush	●	-	□	-	-	□	■	■	■	-
2.4	Reflective label sensor - from top	●	□	□	□	□	-	-	-	-	-
2.5	Adapter 100 mm diameter	●	□	□	□	□	□	□	□	-	-
2.6	Memory card	●	□	□	□	□	□	□	□	□	□
2.7	Standard USB keyboard	●	□	□	□	□	□	□	□	□	□
2.8	External operation panel	●	□	□	□	□	□	□	□	□	□
2.9	Pause adapter PS7 - print job interruption	●	○	□	□	□	□	-	-	-	-
2.10	Tester CC for linear and 2D barcodes	●	□	□	□	-	-	-	-	-	-
<b>Interfaces</b>											
3.1	Centronics according to IEEE 1284	●	□	□	□	□	□	□	-	-	-
3.2	RS422/RS485	●	□	□	□	□	□	□	-	-	-
3.3	Label selection – I/O box	●	□	□	□	□	□	□	□	□	□
3.4	WLAN 802.11b/g	●	□	□	□	□	□	□	□	□	□
<b>Connecting cables</b>											
4.1	Connecting cable RS232 C, 9/9-pin, length 3 m	●	□	□	□	□	□	□	□	□	□
4.2	Patch cable CAT 5e, length 3 m, gray	●	□	□	□	□	□	□	□	□	□
<b>Cutting labels, perforating labels, stacking labels</b>											
5.1	Cutter CU	●	○	□	□	□	□	□	□	□	□
5.2	Cutter tray	●	○	-	□	-	□	-	-	-	-
5.3	Perforation cutter PCU4	●	○	-	□	-	□	□	□	○	-
5.4	Stacker with cutter ST4/L	●	○	-	□	-	-	-	-	□	-
	Stacker with cutter ST4/M	●	-	-	-	-	□	□	□	-	-
5.5	Base frame A4+	●	-	-	□	-	□	□	-	-	-
<b>Rewinding labels, unwinding labels</b>											
6.1	Rewind guide plate for internal rewinding	-	●	□	□	-	-	-	-	-	-
6.2	External rewinder for direct printer connection	●	○	□	□	□	-	-	-	-	-
6.3	External rewinder with built-in power supply	●	○	□	□	□	□	□	□	□	□
6.4	External unwinder for rolls up to 300 mm diameter	●	○	□	□	□	□	□	□	□	□
6.5	Adapter kit A2+, A4+, A6+, A8+	●	○	□	□	□	-	-	-	-	-
6.6	Adapter kit XC4, XC6	●	-	-	-	-	-	-	-	□	□
<b>Dispensing labels</b>											
7.1	Peel-off adapter PS5 for automatic operation	-	●	□	□	-	-	-	-	-	-
7.2	Extended peel-off plate	-	●	□	□	-	-	-	-	-	-
7.3	Present sensor PS6 for manual or automatic operation	-	●	□	□	-	-	-	-	-	-
7.4	Present sensor PS8 for manual operation	-	●	□	□	-	-	-	-	-	-
7.5	Present sensor PS9 variable	-	●	□	□	-	-	-	-	-	-
<b>For dispensing labels</b>											
8.1	Hand switch TR1	-	●	□	□	-	-	-	-	-	-
8.2	Foot switch	-	●	□	□	-	-	-	-	-	-
8.3	Interface connector/15-pin Sub-D plug	-	●	□	□	-	-	-	-	-	-
8.4	Product sensor	-	●	□	□	-	-	-	-	-	-
8.5	Testbox 2 - automatic operation	-	●	□	□	-	-	-	-	-	-
<b>Applicators and dispensing module</b>											
9.1	Dispensing module A5100	-	●	-	□	□	-	-	-	-	-
9.2	All-around labeler	-	●	□	□	-	-	-	-	-	-
9.3	Applicator A1000	-	●	□	□	□	-	-	-	-	-
	Tamp pad A1021 WxH	-	●	□	□	□	-	-	-	-	-
9.4	Universal tamp pad A1021 70x60	-	●	□	□	○	-	-	-	-	-
	Universal tamp pad A1021 90x90	-	●	-	□	○	-	-	-	-	-
	Tamp pad A1321 WxH	-	●	-	□	□	-	-	-	-	-
9.5	Universal tamp pad A1321 116x102	-	●	-	□	○	-	-	-	-	-
	Universal tamp pad A1321 116x152	-	●	-	□	○	-	-	-	-	-
9.6	Blow pad A2021 WxH	-	●	□	□	□	-	-	-	-	-
9.7	Roll-on pad A1411 WxH	-	●	-	□	□	-	-	-	-	-
9.8	Applicator A3200	-	●	□	□	-	-	-	-	-	-
9.9	Tamp pad A3221 WxH	-	●	□	□	-	-	-	-	-	-
9.10	Blow pad A3221 WxH	-	●	□	□	-	-	-	-	-	-
<b>Label dispensers and applicators</b>											
10.1	Mounting plate	-	●	□	□	-	-	-	-	-	-
10.2	Profile 40/80/120 mm	-	●	□	□	-	-	-	-	-	-
10.3	Base plate 500x255 mm	-	●	□	□	-	-	-	-	-	-
10.4	Floor stand 1600	-	●	□	□	□	-	-	-	-	-
10.5	Printer holder A2+, A4+, A6+	-	●	□	□	□	-	-	-	-	-
<b>Software</b>											
11.4	Database Connector	●	●	■	■	■	■	■	■	■	■
11.6	Administration Network Manager	●	●	■	■	■	■	■	■	■	■
	Label software cablabel S3 Lite	●	●	■	■	■	■	■	■	■	■
11.7	Label software cablabel S3 Pro	●	●	□	□	□	□	□	□	□	□
	Label software cablabel S3 Print	●	●	□	□	□	□	□	□	□	□
11.10	Programming manual	●	●	□	□	□	□	□	□	□	□

## Accessories - special equipment, interfaces, connecting cables

Extra equipment	
2.1	 <p><b>Metal cover</b> On request, label printers A4+ and A6+ are available with metal cover (standard with the A8+).</p>
2.2	 <p><b>Print roller DR4-M25</b> For small and thin materials up to 25 mm width</p>
	 <p><b>Print roller DR4-M50</b> For very thin materials from 20 to 50 mm width</p>
	 <p><b>Print roller DR4-M80</b> For very thin materials up to 80 mm width</p>
2.3	 <p><b>Antistatic brush</b> Particularly in case of plastic materials electrostatics is discharged after printing.</p>
2.4	 <p><b>Reflective label sensor</b> From top</p>
2.5	 <p><b>Adapter 100 mm diameter</b> To keep bending to a minimum during stacking it is recommended to use a large core diameter.</p>
2.6	 <p><b>Memory card</b> CompactFlash Type I</p>
2.7	 <p><b>Standard keyboard</b> Connection USB, number of keys 115</p>
2.8	 <p><b>External operation panel</b> If the operation panel is not accessible, after printer installation within a facility, an external one can be connected. Additional slots are available for CompactFlash memory card Type I and host interface.</p>
2.9	 <p><b>Pause adapter PS7</b> For printing in a label loop. Print job is stopped by the pause signal, with the label being printed finished first.</p> <p><b>I/O interface</b>      <b>Inputs:</b>      <b>Outputs:</b> No print job, Pause, external error      printer not ready, print job active</p>
2.10	 <p><b>Tester CC for linear and 2D barcodes</b> A camera testing horizontally and vertically printed barcodes directly after printing. If the code is faulty the print job is stopped and the label removed. The tester CC can be used with tear-off mode, dispensing mode or external rewinder. For further details please refer to the operation manual.</p>
Interfaces	
3.1	 <p><b>Centronics Interface</b> Bi-directional according to IEEE 1284</p>
3.2	 <p><b>RS422/RS485</b> 1,200 to 230,400 baud/8 bit</p>
3.3	 <p><b>Label selection – I/O box</b> From a higher-level control, like a PLC, up to 16 different labels can be selected from the memory card. The I/O box via abc programming enables to realize easy PLC programming with four in- and outputs each.</p>
3.4	 <p><b>WLAN 802.11b/g</b></p>
Connecting cables	
4.1	 <p><b>Connecting cable RS232 C</b>, 9/9-pin, length 3 m</p>
4.2	 <p><b>Patch cable CAT 5e</b>, length 3 m, gray</p>

# Accessories - cutting labels, perforating labels, stacking labels

5.1



## Cutter CU

Used to cut paper labels, self-adhesive labels, cardboard, textile or synthetic materials as well as heat shrink tubes.

### Cutter tray

Up to about 50 labels may be collected in the cutter tray.

Cutter	CU2	CU4		CU6	CU8
Usage	A2+	A4+	A4+M, A4+T XD4T, XC4	A6+ XC6	A8+
Material width up to mm	67	120	110	180	232
Material weight cardboard gr/m²	60-500				
Material thickness mm	0.05-0.8				
Cutting length mm	>5				
Gap height up to mm	2.5				
Cuts/min.	130	120		110	100
Stop print job	When final position of cutter is not reached				
Cutter tray 4 for A4+, A4+M					
Label height up to mm	100				

5.2

## Perforation cutter PCU4

Enables the perforation of the material for later manual separation.

Perforation cutter	PCU4
Usage	A4+, A4+M, A4+T, XD4T, XC4
Material width up to mm	85
Material weight cardboard gr/m <sup>2</sup>	60-300
Material thickness mm	0.05-0.8
Cutting length mm	>5
Gap height up to mm	4.5
Cuts/min.	Cutting 120/perforating 150
Stop print job	When final position of cutter is not reached
Perforating: Web width mm	0.5
Web distances mm	2.5 or 10

5.3



5.4



## Stacker with cutter ST4

Printed materials are cut and stacked. The print job is stopped as soon as the maximum stack height is reached. Even stiff or curved materials may be processed to some extent. We recommend to have your material tested at our facilities.

Stacker with cutter	ST4/L	ST4/M
Usage	A4+, XC4	A4+M, A4+T, XD4T
Material width up to mm	20-110	20-100
Material weight cardboard gr/m <sup>2</sup>	60-300	
Material thickness mm	0.05-0.8	
Cutting length mm	20-150	
Gap height up to mm	1.2	
Cuts/min.	120	
Stop print job	When final position of cutter is not reached, when cover open, when stack height reached	
Stack height up to mm	100	

5.5



### Storage table label WxH

Storage table and protective cover are adapted to the label size and need to be ordered separately.



### Base frame A4+

Used to place the devices on the table in any position.



## Accessories - rewinding labels, unwinding labels

6.1



### Rewind guide plate RG for internal rewinding

Internal rewinding is done by dispensing printers. In this case, the peel-off plate is replaced by the rewind guide plate.

Rewind guide plate	RG2	RG4
Usage	A2+ dispensing version	A4+ dispensing version
Material width up to mm	67	120
Roll diameter up to mm	140	140
Core diameter mm	40	40
Label winding	Outer	

6.2




### External rewinders ER1/2/3 for direct printer connection

The rewriter is directly screwed onto the printer. Labels are optionally wound either inner or outer side. Electronic control by the swing arm ensures a smooth and tight winding.

External rewriter	ER1/210		ER2/210	ER3/210
Usage	A2+	A4+	A6+	A8+
Material width up to mm	67	120	180	235
Roll diameter up to mm	205	205	205	205
Core diameter mm	40/76			
Label winding	Outer or inner			

6.3



### External rewinders ER4/6/8 with built-in power supply

The rewriter may be attached to any external printer. All other technical data according to rewinders ER1/2/3.

External rewriter	ER4/210		ER4/300		ER6/300	ER8/300
Usage	A2+	A4+, A4+M, A4+T, XD4T, XC4	A2+	A4+, A4+M, A4+T, XD4T, XC4	A6+	A8+
Material width up to mm	67	120	67	120	180	235
Roll diameter up to mm	205	205	300	300	300	300
Core diameter mm	40 / 76					
Label winding	Outer or inner					
Operating voltage	100-240 V ~ 50/60 Hz					

For exact alignment of the external rewriter to the printer an adapter kit is offered.

Adapter kit	For A2+, A4+, A6+, A8+
Adapter kit	For XC4, XC6

6.4



### External unwinders EU4/6/8

Ensure a smooth label feed with heavy rolls. Both inner and outer site wound rolls may be used.

External unwinder	EU4/300		EU6/300	EU8/300
Usage	A2+	A4+, A4+M, A4+T	A6+	A8+
Material width up to mm	67	120	180	235
Roll diameter up to mm	300	300	300	300
Core diameter mm	40/76			
Label winding	Outer or inner			






For exact alignment of the external unwinder to the printer an adapter kit is offered.

Adapter kit	For A2+, A4+, A6+, A8+
-------------	------------------------

## Accessories - dispensing labels








- 1 Dispensing printers ("P" types) additionally need to have a peel-off adapter or present sensor. Different types for either manual operation, or via hand switch, foot switch or an external signal are available.

Dispensing labels																
7.1	<div></div> <div><p><b>Peel-off adapter PS5 for automatic operation</b></p><p>Printing and dispensing the label is triggered via external signal. The label is removed by an applicator or robot.</p><table><tr><td><b>I/O interface</b></td><td><b>Inputs:</b></td><td><b>Outputs:</b></td></tr><tr><td></td><td>Start</td><td>No print job</td></tr><tr><td></td><td>Label removed</td><td>Printer not ready</td></tr><tr><td></td><td>External error</td><td>Print job active</td></tr><tr><td></td><td></td><td>Label in dispensing position</td></tr></table></div>	<b>I/O interface</b>	<b>Inputs:</b>	<b>Outputs:</b>		Start	No print job		Label removed	Printer not ready		External error	Print job active			Label in dispensing position
<b>I/O interface</b>	<b>Inputs:</b>	<b>Outputs:</b>														
	Start	No print job														
	Label removed	Printer not ready														
	External error	Print job active														
		Label in dispensing position														
7.2	<div></div> <div><p><b>Extended peel-off plate</b></p><p>For labels particularly difficult to remove from liner the peel-off plate with rewind guide plate, extended by 10 mm, is used. Only in connection with present adapter PS5 or an applicator.</p></div>															
7.3	<div></div> <div><p><b>Present sensor PS6</b></p><p><b>1. Manual operation</b></p><p>The present sensor detects the label being in dispensing position and interrupts the print job. As soon as the label has been manually removed the next one is printed immediately.</p><p><b>2. Automatic operation</b></p><p>Dispensing via hand switch, foot switch, or an external signal</p><table><tr><td><b>I/O interface</b></td><td><b>Inputs:</b></td><td><b>Outputs:</b></td></tr><tr><td></td><td>Start</td><td>No print job</td></tr><tr><td></td><td>External error</td><td>Printer not ready</td></tr><tr><td></td><td></td><td>Print job active</td></tr><tr><td></td><td></td><td>Label in dispensing position</td></tr></table></div>	<b>I/O interface</b>	<b>Inputs:</b>	<b>Outputs:</b>		Start	No print job		External error	Printer not ready			Print job active			Label in dispensing position
<b>I/O interface</b>	<b>Inputs:</b>	<b>Outputs:</b>														
	Start	No print job														
	External error	Printer not ready														
		Print job active														
		Label in dispensing position														
7.4	<div></div> <div><p><b>Present sensor PS8 for manual operation</b></p><p>The present sensor detects the label being in dispensing position and interrupts the print job. As soon as the label has been manually removed the next one is printed immediately.</p></div>															
7.5	<div></div> <div><p><b>Present sensor PS9 variable</b></p><p>For dispensing e.g. round labels where the leading edge of the label cannot be detected by the PS8. Extension is customized.</p></div>															

# Accessories - for dispensing labels

For peel-off adapter PS5,  
present sensor PS6,  
pause adapter PS7,

dispensing modules A5104/A5106,  
applicator A1000,  
applicator A3200

For dispensing labels	
8.1	 <b>Hand switch TR1</b> Printing and dispensing on demand
8.2	 <b>Foot switch</b> Printing and dispensing on demand
8.3	 <b>Interface connector/Sub-D plug</b> Sub-D plug 15-pin with screw clamps for PS5, PS6, PS7 and applicators. To connect external control signals.
8.4	 <b>Product sensor</b> For automatic product detection on the conveyor belt
8.5	 <b>Testbox 2</b> Simulation of automatic operation



## Dispensing module with peel-off adapter PS5

For labeling packages on a conveyor belt. The product sensor triggers the printing process. Labeling is started and at the same time the next label is printed. Conveyor speed and print speed need to be synchronized.

	A5104	A5106
Usage	A4+	A6+
Label width mm	25-116	50-176
Label height mm	25-200	
Product surface	Flat	
Product height	Fixed	
Product during labeling	In motion with speed synchronized to printer	




## All-around labeler

Combined with the A1000 applicator labels on cylindrical objects around the entire circumference of 360° can be applied. The product is put on the rolls and labeling is started via hand or foot switch.

All-around labeler	
Usage	A2+, A4+ with applicator A1000-220
Product diameter mm	12-40
Product surface	Cylindrical
Product during labeling	In rotary motion
Tamp pad A1021 WxH	
Label width mm	25-116
Label height mm	25-140

# Applicator A1000

9.3



## Real-time application

Combined with the A2+, A4+ and A6+ printers the A1000 applicator means a cost-effective solution - for both semi-automatic operation and integration into product lines. For operation compressed air of 4,5 bar is needed.

### 1 Long service life

The ball-bearing guide bars are low-wearing.

### 2 Variable product heights

The lifting cylinder allows labeling at different heights. Different stroke heights are available.

### 3 Pre-dispensing button

For testing the labeling process. Pushing the button the first time causes the label to be printed and held by the pad. Pushing the button again starts the application.

### 4 Compressed air regulation unit

Microfilters prevent contamination. The compressed air regulator ensures a permanent high labeling quality.

### 5 High process reliability

The supporting air jet stream, induction air and lifting speed can be adjusted. The pressure can be reduced to less than 10 N (1 kg) for highly sensitive products and packages. To avoid contamination of the vacuum holes, these are cleaned with air pressure after each application.

### 6 Label sizes

Labels with 25 to 176 mm width and 25 to 200 mm height can be applied.

### 7 Supporting air

Used for blowing the label onto the pad

### 8 Digital I/O interface

A PLC, sensor or hand switch starts the labeling. At the same time, status and error messages are issued.

#### Inputs:

- Start
- Print first label
- External error
- Stop (external error)
- External reset only for 25-pin

#### Outputs:

- Printer not ready
- No print job
- Collective alarm
- Home position reached
- Labeling position reached
- Labeling error

Applicator	A1000-220	A1000-300	A1000-400
Usage	A2+, A4+, A6+	A2+, A4+, A6+	A2+, A4+, A6+
Cylinder stroke	mm	220	300
Tamp stroke	mm	70	150
below device	mm	250	
Compressed air	bar	4.5	



## Accessories - Applicator A1000

9.4



### Tamps

Labels are applied on the tamp and held by vacuum. Tamp and label are then moved to the product by applicator.

#### Universal tamp pad

The rasterized vacuum holes are covered by a foil and are pierced according to the label size.

**Tamp pads** are manufactured according to the label size.

	Universal tamp pads			Tamp pad		
	A1021 70x60	A1021 90x90		A1021 WxH		
Usage	A2+	A4+	A4+	A2+	A4+	A6+
Label width mm	25-63	25-70	25-90	25-63	25-116	50-176
Label height mm	25-60		25-90	25-200		
Product surface	Flat					
Product height	Variable					
Product during labeling	Not moving					

9.5



### Tamp spring-mounted

The spring deflection allows labeling even on inclined surfaces.

#### Universal tamp pad

The rasterized vacuum holes are covered by a foil and are pierced according to the label size.

**Tamp pads** are manufactured according to the label size.

		Universal tamp pads		Tamp pad	
		A1321 116x102	A1321 116x152	A1321 WxH	
Usage		A4+	A4+	A4+	A6+
Label width	mm	25-116	25-116	25-116	50-176
Label height	mm	25-102	25-152	25-200	
Product surface		Flat			
Product height		Variable			
Product during labeling		Not moving			

9.6



### Blow pad

In case of pressure-sensitive products, the label can be blown on.

Thus, the blow pad moves to a fixed height. The product to be printed is positioned about 10 mm below.

Blow pad	A2021		
Usage	A2+	A4+	A6+
Label width mm	25-63	25-116	50-176
Label height mm	25-100		
Product surface	Flat		
Product height	Fixed		
Product during labeling	Not moving or in motion		

9.7



### Roll-on pad

Using the roll-on pad the label is moved to below the roll. The pad moves onto the product and the label is rolled on during transport.

Roll-on pad	A1411	
Usage	A4+	A6+
Label width mm	25-116	50-76
Label height mm	80-200	80-200
Product surface	Flat	
Product height	Variable	
Product during labeling	In motion	

# Applicator A3200

9.8



## Real-time application

With the A3200 applicator labels that are printed with the A2+ or A4+ printers are automatically applied on a product. A rotary cylinder allows positioning the label between 45° and 95°. Finally, the label is placed on the product via short stroke cylinder.

- 1 Long service life**  
The ball-bearing guides are low-wearing.
- 2 Variable angular position**  
The rotary cylinder allows labeling on horizontal, inclined and vertical surfaces.
- 3 Pre-dispensing button**  
For testing the labelling process. Pushing the button the first time causes the label to be printed and held by the pad. Pushing the button again starts the application.
- 4 Compressed air regulation unit**  
Microfilters prevent contamination. The compressed air regulator ensures a permanent high labeling quality.
- 5 High process reliability**  
The supporting air jet stream, induction air and lifting speed can be adjusted. The pressure can be reduced to less than 10 N (1 kg) for highly sensitive products and packaging. To avoid contamination of the vacuum holes, these are cleaned with air pressure after each application.
- 6 Label sizes**  
Labels with 4 to 116 mm width and 5 to 80 mm height can be applied.
- 7 Supporting air**  
Used for blowing the label onto the pad
- 8 Digital I/O interface**  
A PLC, sensor or hand switch starts the labeling. At the same time, status and error messages are issued.

### Inputs:

- Start
- Print first label
- External error
- Stop (external error)
- External reset only for 25-pin

### Outputs:

- Printer not ready
- No print job
- Collective alarm
- Home position reached
- Labeling position reached
- Labeling error

Applicator	A3200
Usage	A2+, A4+
Rotary cylinder	45°-95°
Lifting cylinder up to mm	30
Compressed air bar	4.5

Tamp pads or blow pads are manufactured according to the label size.

	Tamp pad A3221		Blow pad A3221	
Usage	A2+	A4+	A2+	A4+
Label width mm	4-63	20-116	10-63	20-16
Label height mm	5-80		10-80	
Product surface	Flat			
Product during labeling	Not moving		In motion	

9.9

9.10



## Accessories - mounting equipment

10.1



### Mounting foot (for A2+, A4+)

For fastening the print and apply system and product holder.

#### 1 Mounting plate

The print and apply system is fastened on the mounting plate.

10.2



#### 2 Profile

Standard lengths 40, 80, 120 mm. The aluminum square profile can also be manufactured in other lengths upon request.

10.3



#### 3 Base plate

For fastening the product holder  
Standard size 500x255 mm

10.4



### Floor stand

Enables the printer to be quickly and flexibly integrated into any manufacturing line. Height and width of the labeling position are easy to adjust. Four guide rollers at the chassis provide for mobility. The floor stand is adjusted with adjustable feet at the place of operation.

Floor stand		1600
Total height	mm	1600
Labeling height	up to mm	1400
Projection until middle of label	mm	230-500
Chassis WxDxH	mm	600x860x140

10.5



### Printer holder

The A2+, A4+ or A6+ label printers are fixed on the plate and quicklocked.

# Label software cablabel S3



cablabel S3 concentrates label design, print control and monitoring of all cab marking systems. The development of devices and software is synchronized.

## Highlights

Like no other software available cablabel S3 develops the full potential of cab devices. The software utilizes the JavaScript code to the full extent. The Pro product imports existing JavaScript files, so you can switch over easily to new software. With the new layer technology the user designs a label which works for all established devices and resolutions. Intelligent print control evaluates both device and resolution for printout and provides the proper data. Thus, possible sources of error are reduced.

cablabel S3 also maximizes the integration of database connections via Database Connector. After designing the label, the software provides all files to be stored within the printer for database connections. Stand-alone operation independent from a host system is supported. In addition the software creates interfaces which are easy to handle for SAP connection or other devices like PLC, scales and barcode testers.

## Functional range

Every company designs and formats their label printing differently. For example, label creation and production are executed by different employees. To adopt the software package to specific needs, cab offers different software packages.

- *cablabel S3 Lite* is offered free of costs with every cab printer and allows to create and print labels.
- With cost-saving *cablabel S3 Pro* label designs for professional technical solutions can be created.
- *cablabel S3 Viewer* shows the preview of a label in the Windows Explorer and - like the Lite product - is delivered free of costs with every cab printer. The Viewer may support showing examples during the approval processes or supplier requirements.
- *cablabel S3 Print* is provided for users in production or warehouse. The user interface is simplified and provides only those functions which are required for label printing.

Other products like cablabel S3 Pro Laser, Print Laser and Print Server are in preparation.



# Integration



No printer works isolated. In a productive environment it is connected to other equipment or networks for control and monitoring. cab offers various possibilities to integrate the printer into your business environment.

## Control

Every cab printer can be directly coded with the simple programming language *JScript* and an extensive instruction set. Direct programming is supported by cablabel S3, but may also be created with any text editor.

As an integrated element of the firmware, the *abc Basic Compiler* enables the printer to process data via BASIC programming before it is sent for print editing. That way, you replace external printer languages or integrate data from other systems, e.g. scale or PLC.

**11.4** The *Database Connector* enables printers to access data directly from a central ODBC- or OLEDB compatible database and to print it as a label.

In cooperation with SAP\* cab developed the so-called *replace method* to control cab printers quickly and easily from SAPScript using SAP R/3. Using this method the host computer only sends the JScript variable, respectively changed data to the printer. As a Silver Level Partner in SAP's printer vendor program, cab has access to SAP development environments for optimum printer support.

\* SAP and all SAP logos are trademarks or registered trademarks of SAP SE in Germany and in several other countries.

**11.10** The *Programming manual* explains and describes commands for different printer models via direct programming with JScript and abc and the connection of the printer to databases via Database Connector.

For printer control via PC drivers are available for Windows operating systems. For A+ printers in addition CUPS-based drivers for Mac OS X and Linux. The drivers ensure optimum stability on your operating system.

## Monitoring

Using standard programs such as the web browser or FTP clients, the integrated HTTP and FTP servers enable printer monitoring and configuration, firmware updates and memory card administration. Status, warning and error messages are sent to administrators or users via e-mails or SNMP datagrams via SNMP and SMTP clients. A time server is used to synchronize time and date.

**11.6** The *Administration Network Manager* enables the user to control a number of printers across a network simultaneously. It supports monitoring, configuration, firmware updates, memory card administration, file synchronization and PIN administration centrally.

## Stand-alone operation



### Printing without PC

Stand-alone operation is the ability of cab printers to print labels even if these devices are not connected to the host system.

The layout is designed with a special label software or direct programming via PC.

Label formats, fonts, text and graphics data as well as database contents are saved or read on the CompactFlash memory card, USB stick or internal IFFS printer memory.

Only variable data to be printed is sent to the printer via keyboard or host. Additionally, data sent by a barcode scanner or scale can be processed.

## Easy maintenance



### Label sensor

For cleaning the label sensor is unlocked and pulled out with slight finger pressure.



### Print head

The print head may be exchanged in just few steps. No need of adjustments and settings.



### Print roller

Three screws allow an easy and fast removing of the print roller for cleaning or replacement.



### Assembling tool

For replacing wear parts or mounting peripherals ONE single tool is inserted in the printer ready to hand.

## Service















Well-trained cab service engineers give worldwide support in maintenance and repair. Please send your printer to one of cab's service centres or one of our selected service partners. We will check and repair your printer within a few days. If requested, we will make a temporary equivalent device available for the time of repair.

## Training



We offer information on the programming of different software tools, printer drivers and label layout design. Enhance your knowledge on cab printers to make more effective use of cab printers. We also offer seminars for maintenance and repair.

## Label printers - product range

		Part no.	Printers	dpi	Part no.	Print heads	dpi	Part no.	Wear parts
1.1		5954511	Label printer A2+	300	5954105.001	Print head 2	300	5954102.001 5954104.001	Print roller DR2 Rewind assist roller RR2
		5954512	Label printer A2+	300P					
		5954575	Label printer A2+	600	5958686.001	Print head 2	600		
		5954578	Label printer A2+	600P					
1.2		5954500	Label printer A4+	200	5954081.001	Print head 4	203	5954180.001 5954183.001	Print roller DR4 Rewind assist roller RR4
		5954505	Label printer A4+	200P					
		5954501	Label printer A4+	300	5954072.001	Print head 4	300		
		5954506	Label printer A4+	300P					
		5954502	Label printer A4+	600	5954077.001	Print head 4	600		
		5954507	Label printer A4+	600P					
		5954524	Label printer A4.3+	200	5954085.001	Print head 4.3	203		
		5954526	Label printer A4.3+	200P					
1.3		5954587	Label printer A6+	200	5954217.001	Print head 6	203	5954245.001 5954246.001	Print roller DR6 Rewind assist roller RR6
		5954588	Label printer A6+	200P					
		5954513	Label printer A6+	300	5954106.001	Print head 6	300		
		5954514	Label printer A6+	300P					
1.4		5954517.101	Label printer A8+ with metal cover	300	5954107.001	Print head 8	300	5954103.001	Print roller DR8
1.5		5954552	Label printer A4+M	300	5954072.001 5954077.001	Print head 4	300	5954180.001 5954183.001	Print roller DR4 Rewind assist roller RR4
		5954554	Label printer A4+M	600		Print head 4	600		
1.7		5954568	Label printer A4+T	300	5954072.001 5954077.001	Print head 4	300	5954180.001	Print roller DR4
		5954570	Label printer A4+T	600		Print head 4	600		
1.8		5959970	Label printer XD4T	300	5954072.001	Print head 4	300	5954180.001	Print roller DR4
1.9		5965700	Label printer XC4	300	5954072.001	Print head 4	300	5954180.001	Print roller DR4
1.10		5965701	Label printer XC6	300	5954106.001	Print head 6	300	5954245.001	Print roller DR6
		Part no.	Special printers		<b>Scope of delivery:</b> Label printer, power cable E+F type, length 1,8 m, connecting cable USB, length 1,8 m, operation manual de/en  <b>DVD:</b> Operation manual in more than 20 languages (only with A+ series), operation manual de/en/fr/es/it (with X series) configuration manual de/en/fr, service manual de/en, spare parts list de/en, programming manual en, printer drivers 32/64 bit in more than 20 languages for Windows Vista      Server 2003 Windows 7            Server 2008 Windows 8            Server 2008 R2 Windows 8.1          Server 2012 Windows 10           Server 2012 R2 Mac OS X drivers de/en/fr (only with A+ series), Linux drivers de/en/fr (only with A+ series), Label software cablabel S3 Lite, cablabel S3 Viewer Database Connector				
1.11		59545xx.101*	Printer with metal cover for A4+, A4+M, A4+T or A6+						
1.12		595xxxx*	Label printer for thermal direct printing on request						

\* Instead of "x" please choose the article no. of the cab printer as listed above.

\* Instead of "x" please choose the article no. of the cab printer as listed above.

## Accessories - product range

		Part no.	Special equipment
2.1		<b>5954012.001</b> <b>5954013.001</b>	Metal cover for A4+ Metal cover for A6+
2.2		<b>5953700.001</b>	Print roller DR4-M25
		<b>5953701.001</b>	Print roller DR4-M50
		<b>5953702.001</b>	Print roller DR4-M80
2.3		<b>5958678</b>	Antistatic brush
2.4		<b>5958631</b>	Reflective label sensor from top
2.5		<b>5959622.001</b>	Adapter 100
2.6		<b>5561043</b>	Memory card CompactFlash Type I
2.7		<b>5901626</b>	Standard USB keyboard German version
2.8		<b>5954380</b>	External operation panel
2.9		<b>5946146</b>	Pause adapter PS7
2.10		<b>5571005</b> <b>5571000</b>	Barcode tester CC2 Barcode tester CC4
		Part no.	Interfaces
3.1		<b>5954200</b>	Centronics according to IEEE 1284
3.2		<b>5954201</b>	RS422/RS485
3.3		<b>5954191</b>	Label selection – I/O box
3.4		<b>5561041</b>	WLAN 802.11b/g
		Part no.	Connecting cables
4.1		<b>5550818</b>	Connecting cable RS232 C 9/9-pin, length 3 m
4.2		<b>5918008</b>	Patch cable CAT 5e, length 3 m, gray
		Part no.	Cutting, perforating, stacking
5.1		<b>5948382</b> <b>5948000</b> <b>5948001</b> <b>5948002</b>	Cutter CU2 Cutter CU4 Cutter CU6 Cutter CU8
5.2		<b>5946995</b>	Cutter tray 4
5.3		<b>5960050.351</b> <b>5960050.352</b>	Perforation cutter PCU4/2,5 Perforation cutter PCU4/10
5.4		<b>5541311</b> <b>5541313</b>	Stacker with cutter ST4/L Stacker with cutter ST4/M
		<b>55xxxxx**</b> <b>55xxxxx**</b>	Storage table ST4/L, label WxH Storage table ST4/M, label WxH
5.5		<b>5958932</b>	Base frame A4+







\*\* User specific article no. following request

		Part no.	Rewinding labels, unwinding labels
6.1		<b>5954108.001</b> <b>5954190.001</b>	Rewind guide plate RG2 for internal rewinding Rewind guide plate RG4 for internal rewinding
6.2		<b>5948102</b> <b>5943251</b> <b>5945802</b>	External rewinder ER1/210 External rewinder ER2/210 External rewinder ER3/210
6.3		<b>5948100</b> <b>5946090</b> <b>5946420</b> <b>5945804</b>	External rewinder ER4/210 External rewinder ER4/300 External rewinder ER6/300 External rewinder ER8/300
6.4		<b>5946091</b> <b>5946421</b> <b>5945806</b>	External unwinder EU4/300 External unwinder EU6/300 External unwinder EU8/300
6.5		<b>5948170</b>	Adapter kit for A2+, A4+, A6+, A8+
6.6		<b>5965712</b> <b>5965713</b>	Adapter kit for XC4 Adapter kit for XC6
		Part no.	Dispensing labels
7.1		<b>5946120</b>	Peel-off adapter PS5 Automatic operation
7.2		<b>5958772</b> <b>5948830</b> <b>5958565</b>	Extended peel-off plate A2+ Extended peel-off plate A4+ Extended peel-off plate A6+
7.3		<b>5942353</b>	Present sensor PS6 Manual/automatic operation
7.4		<b>5946900</b>	Present sensor PS8 Manual operation
7.5		<b>5948595</b>	Present sensor PS9 Variable
		Part no.	Accessories for dispensing labels
8.1		<b>5942345</b>	Hand switch TR1
8.2		<b>5535901</b>	Foot switch
8.3		<b>5917652</b>	Interface connector 15-pin SUB-D plug Phoenix Contact 2761606
8.4		<b>5941526</b>	Product sensor
8.5		<b>5533240</b>	Testbox 2 Automatic operation



## Accessories - product range

		Part no.	Applicators and dispensing modules
9.1		<b>5949281</b> <b>5949265</b>	Dispensing module A5104 Dispensing module A5106
9.2		<b>5941345</b>	All-around labeler
9.3		<b>5949001</b> <b>5949002</b> <b>5949003</b>	Applicator A1000-220 Applicator A1000-300 Applicator A1000-400
9.4		<b>5xxxxxx**</b>	Tamp pad A1021 WxH
		<b>5949072</b>	Universal tamp pad A1021 70x60
		<b>5949075</b>	Universal tamp pad A1021 90x90
9.5		<b>5xxxxxx**</b>	Tamp pad A1321 WxH
		<b>5949076</b>	Universal tamp pad A1321 116x102
		<b>5949077</b>	Universal tamp pad A1321 116x152
9.6		<b>5xxxxxx**</b>	Blow pad A2021 WxH
9.7		<b>5xxxxxx**</b>	Roll-on pad A1411 WxH
9.8		<b>5976050</b>	Applicator A3200
9.9		<b>5xxxxxx**</b>	Tamp pad A3221 WxH
9.10		<b>5xxxxxx**</b>	Blow pad A3221 WxH

		Part no.	Mounting equipment
10.1		<b>5969811</b> <b>5958367</b>	Mounting plate for A2+ Mounting plate for A4+
10.2		<b>5958365</b> <b>5965929</b> <b>5971136</b>	Profile 40 Profile 80 Profile 120
		<b>5xxxxxx**</b>	Profile L
10.3		<b>5961203</b>	Base plate 500x255
10.4		<b>5947400</b>	Floor stand 1600
10.5		<b>8914422</b> <b>8913693</b> <b>8914423</b>	Printer holder for A2+ Printer holder for A4+ Printer holder for A6+
		Part no.	Label software
11.7		<b>5588000</b>	cablabel S3 Lite
		<b>5588001</b>	cablabel S3 Pro 1 WS
		<b>5588100</b>	cablabel S3 Pro 5 WS
		<b>5588101</b>	cablabel S3 Pro 10 WS
		<b>5588150</b>	cablabel S3 Pro 1 additional licence
		<b>5588151</b>	cablabel S3 Pro 4 additional licences
		<b>5588152</b>	cablabel S3 Pro 9 additional licences
		<b>5588002</b>	cablabel S3 Print 1 WS
		<b>5588105</b>	cablabel S3 Print 5 WS
		<b>5588106</b>	cablabel S3 Print 10 WS
		<b>5588155</b>	cablabel S3 Print 1 additional licence
		<b>5588156</b>	cablabel S3 Print 4 additional licences
		<b>5588157</b>	cablabel S3 Print 9 additional licences
		In preparation	cablabel S3 Print Server
11.10		<b>9008486</b>	Programming manual en, printed copy

\*\* User specific article no. following request

# Product overview

Label printers MACH1/2  
in the lower price segment



Label printers MACH4  
where little space is available



Label printers EOS1  
desktop device for label rolls  
up to diameter 155 mm



Label printers EOS4  
desktop device for label rolls  
up to diameter 210 mm



Label printers A2+  
industrial device  
up to print width 57 mm



Label printers SQUIX  
industrial device  
up to print width 108 mm



Label printers A6+  
industrial device  
up to print width 168 mm



Label printers A8+  
industrial device  
up to print width 216 mm



Label printers XD4T  
for double-sided printing



Label printers XC  
for two-color printing



Print and apply systems Hermes+  
for automation



Print and apply systems Hermes C  
for two-color printing and applying



Print modules PX  
to be integrated  
in automatic labeling systems



Labels  
of more than 400 materials



Ribbons  
in wax, resin and resin/wax qualities



Label software cablabel S3  
Design, print, monitoring



Label dispensers HS/VS  
for horizontal or  
vertical dispensing



Labeling heads IXOR  
to be integrated  
in labeling machines




Marking lasers FL+  
with output powers 10 to 50 watt



Laser marking systems  
for industrial solutions



 Headquarters and fabrication in Germany

 to  International subsidiaries

There are further 820 distribution partners in more than 80 countries.



## Europe

### Germany

cab Produkttechnik GmbH & Co KG  
Wilhelm-Schickard-Str. 14  
76131 Karlsruhe  
phone +49 721 6626 0  
fax +49 721 6626 129  
[info@cab.de](mailto:info@cab.de)  
[www.cab.de](http://www.cab.de)

### France

cab Technologies S.à.r.l.  
2a Rue de la Moder  
Z.A. Nord du Val de Moder  
67350 Niedermodern  
phone +33 388 722501  
fax +33 388 722502  
[info.fr@cab.de](mailto:info.fr@cab.de)  
[www.cab.de/fr](http://www.cab.de/fr)

## America

### USA

cab Technology, Inc.  
87 Progress Avenue Unit 1  
Tyngsboro, MA 01879  
phone +1 978 649 0293  
fax +1 978 649 0294  
[info.us@cab.de](mailto:info.us@cab.de)  
[www.cab.de/us](http://www.cab.de/us)

### Latin America

Alejandro Balmaceda  
Hacienda Jurica Pte 1615  
Colonial de Valle  
32553 Juárez, Mexico  
phone +52 656 682 4301  
[a.balmaceda@cab.de](mailto:a.balmaceda@cab.de)  
[www.cab.de/es](http://www.cab.de/es)

## Asia

### Taiwan

cab Technology Co., Ltd.  
希愛比科技股份有限公司  
16F-1, No. 700, Jhong Jheng Rd  
Junghe, Taipei 23552  
phone +886 (02) 8227 3966  
fax +886 (02) 8227 3566  
[info.asia@cab.de](mailto:info.asia@cab.de)  
[www.cab.de/tw](http://www.cab.de/tw)

### China

cab (Shanghai) Trading Co., Ltd.  
铠博(上海)贸易有限公司  
A507, No. 268, Tong Xie Rd  
Shanghai 200335  
phone +86 (021) 6236 3161  
fax +86 (021) 6236 3162  
[info.cn@cab.de](mailto:info.cn@cab.de)  
[www.cab.de/cn](http://www.cab.de/cn)

cab (Shanghai) Trading Co., Ltd.  
铠博(上海)贸易有限公司  
Room 39, 10F, 8 Lin He Zhong Rd  
Tian He District, Guangzhou 510610  
phone +86 (020) 2831 7358  
[info.cn@cab.de](mailto:info.cn@cab.de)  
[www.cab.de/cn](http://www.cab.de/cn)

## Africa

### South Africa

cab Technology (Pty) Ltd.  
14 Republic Street  
Bordeaux  
2125 Randburg  
phone +27 11 886 3580  
fax +27 11 789 3913  
[info.za@cab.de](mailto:info.za@cab.de)  
[www.cab.de/za](http://www.cab.de/za)