

CABLED SCANNERS

# C-37

## Barcode CCD Scanner

### HIGHLIGHTS

200 scans per second

1.5 m drop proof

Lightweight



 **OPTICON**

# C-37

## Basic product specifications

### OPERATING INDICATORS

**VISUAL:** 1 LED (red/green/orange) **NON-VISUAL:** Buzzer

### OPERATING KEYS

**ENTRY OPTIONS:** 1 scan key

### COMMUNICATION

**RS232:** DB9 PTF connector with external power supply **KEYBOARD WEDGE:** MiniDIN6 F/M connector **USB:** Ver. 1.1, HID/VCP, USB-A connector

### POWER

**VOLTAGE REQUIREMENT:** 5V  $\pm$  10% (Keyboard Wedge and USB), 6V (min. 4.5, max. 6.6V) (RS232)

### BARCODE SCANNER OPTICS

**LIGHT SOURCE:** 630 nm red LED **SCAN METHOD:** CCD linear Sensor 2500 Pixels **SCAN RATE:** 200 scans/sec **TRIGGER MODE:** Manual, auto-trigger **READING PITCH ANGLE:** -30 to 0°, 0 to +30° **READING SKEW ANGLE:** -70 to -20°, 20 to +70° **READING TILT ANGLE:** -25 to 0°, 0 to +25° **CURVATURE:** R>15 mm (EAN8), R>20 mm (EAN13) **MIN. RESOLUTION AT PCS 0.9:** 0.125 mm / 5 mil **DEPTH OF FIELD:** At PCS 0.9, Code 39  
0 - 15 mm / 0 - 0.59 in

### SUPPORTED SYMBOLOGIES

**BARCODE (1D):** JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSM-ISSN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey **POSTAL CODE:** Chinese Post, Korean Postal Authority code

### DURABILITY

**TEMPERATURE IN OPERATION:** 0 to 50 °C / 32 to 122 °F **TEMPERATURE IN STORAGE:** -20 to 60 °C / -14 to 140 °F **HUMIDITY IN OPERATION:** 5 - 95% (non-condensing) **HUMIDITY IN STORAGE:** 5 - 95% (non-condensing) **AMBIENT LIGHT IMMUNITY:** Fluorescent 10,000 lx max, Incandescent 10,000 lx max **DROP TEST:** 1.5 m / 5 ft drop onto concrete surface **VIBRATION TEST:** 10 - 100 Hz with 2G for 1 hour **PROTECTION RATE:** IP 42

### PHYSICAL

**DIMENSIONS (W X H X D):** 53 x 75 x 150 mm / 2.09 x 2.95 x 5.91 in **WEIGHT BODY:** Ca. 90 g / 3.2 oz (excl. cable) **CASE:** ABS, Black, White

### REGULATORY & SAFETY

**PRODUCT COMPLIANCE:** CE, FCC, VCCI, RoHS

### ENCLOSED ITEMS

**POWER SUPPLY:** 100-240V/0.5A, 50/60 Hz, 6V/2A (for RS232)

### MODELS

**INTERFACE VERSIONS:** RS232, Keyboard Wedge, USB **COLOR VERSIONS:** Black, White

\_C-37\_001

© COPYRIGHT OPTICON. ALL RIGHTS RESERVED. THIS INFORMATION IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. FOR AVAILABILITY, CONTACT YOUR LOCAL REPRESENTATIVE.

