

TC75 Series Rugged Touch Computer

YOUR FRONT LINE TO A SMARTER ENTERPRISE

Your field workforce needs a mobile computer to access the people and information required to maximize efficiency and better serve your customers. You want to give them an enterprise-class handheld built for life out in the field — yet your workers expect a device that is every bit as refined and easy-to-use as their own consumer smartphone. The TC75 Series is the Android[™] enterprise touch computer that delivers it all. A choice of Android OS, fortified for use in the enterprise. A rugged design that delivers reliable everyday operation. Anywhere anytime access to virtually any information in your back-end systems. The ability to capture more types of data faster than ever before. Instant push-to-talk communications with co-workers out in the field as well as supervisors, dispatch and more back in the office. 4G LTE support for a robust wireless connection on the world's fastest cellular networks. And a full complement of accessories meets the unique needs of virtually any mobile worker. The TC75 Series — the easy way to empower your field teams with a true mobile office.



TC75x

Mx — Making Android a More Robust Enterprise OS

Every TC75 Series ships with Mobility Extensions (Mx), a series of features that make Android a more robust enterpriseclass operating system. Mx minimizes IT support time and maximizes worker productivity and device uptime by providing better control of your mobile devices, application access and Wi-Fi performance and security. Standard Configuration TC75 and TC75x devices come with Google Mobile Services (GMS) and Android for Work (AFW). GMS provides integrated Google applications such as Gmail and Google Maps, and AFW adds more enterprise-class features. Professional Configuration TC75 and TC75x devices ship without GMS and AFW, promoting greater privacy and security of personal information.

World-class Data Capture

An integrated enterprise-class imager offers Zebra's proprietary PRZM Intelligent Imaging technology, a megapixel sensor and advanced optics, enabling the lightning-fast capture of 1D and 2D barcodes in virtually any condition. The rear-facing color camera enables the easy capture of highresolution photos, signatures, videos and more, so workers can capture more types of business intelligence to streamline more business processes. The front camera allows workers to place a video call to get the on-the-spot assistance they need. And Near Field Communications automates identity verification at facility entry points.

Maximum Data Entry Flexibility with an Industry Leading Dual Mode Touch Panel

Let your users choose their preferred data input pair: finger and gloved finger or finger and stylus — ideal for crisp signature capture. The intelligent 4.7 in. display automatically adjusts as needed, unlike competitive devices that require setting adjustments every time the user switches data input method.

Automatically Capture Data and Process Entire Documents

With SimulScan Document Capture, your workers can simultaneously capture barcodes, text fields, phone numbers, images, signatures and even check boxes in the time it takes to press a button, improving invoicing speed, order speed and more.

Superior Audio Quality and Functionality for a New Level of Voice Flexibility

Up to four times the loudness of popular smartphones and noise cancelling technology provides crystal clear audio on both ends of every call. Support for Workforce Connect Push-to-Talk (PTT) Express and Pro provides an instant connection to co-workers in the field, plus supervisors and other support staff back in the office.

Mobility DNA

Every strand of your mobility platform is simpler with Zebra's Mobility DNA. That's because, from the start, you have the industry's most comprehensive suite of mobility must-haves to

accelerate your solution. More off-the shelf end-user apps, more robust administration utilities and easier app development. Purpose built for the enterprise, Mobility DNA makes ease, confidence and value intrinsic to your investment and our full line of Android mobile computers.

A Robust Accessory Family for Easy On-the-Go Device Management

Accessories include a flexible vehicle cradle for charging — even with snap-on accessories attached. A magnetic stripe reader enables mobile payment.¹ The field attachable trigger handle brings comfort to scan intensive tasks. Select Zebra Bluetooth printers enable anywhere anytime printing. And backroom management is easier and more cost effective than ever thanks to our unique ShareCradle System that accommodates the TC75 Series and future Zebra devices.

Rugged and Ready for All-day Every Day Use Out in the Field

The TC75 Series delivers reliable operation, even after multiple 8 ft./2.4 m drops to concrete and 2,000 consecutive 3.2 ft./1 m tumbles in our punishing tumble test. With IP65 and IP67 sealing, the TC75 Series is dusttight and can survive complete immersion in water. And the Corning Gorilla Glass touch panel and scanner exit window bring a new level of durability to two of the most vulnerable components on any handheld device.

THE TC75 SERIES — THE RIGHT DEVICE MAKES ALL THE DIFFERENCE.

For more information, visit www.zebra.com/tc75series or access our global contact directory at www.zebra.com/contact

Boost efficiency and customer service with the TC75 Series in:

T&L

- Proof of delivery
- Asset management
 Asset tracking
- Scheduling
- Routing
- Location services

Field Service

- Asset management
- Parts inventory
- Invoicing
- Task management
 Location based
- services
- Technical assistance
- Appointment scheduling
- Service automation

Direct Store Distribution (DSD)/ Route Accounting

- Order automation
- Delivery tracking
- Inventory management
- Store setupCustomer support

Government and Public Safety

- Alternate to
- two-way radio
- Data collection
- Records query
- Real time data
- and voice
- ID validation/ ticketing
- Location services Resource
- deployment • Document on
- the scene video and photos

TC75 Series Specifications

Dimensions	6.3 in. L x 3.3 in. W x 1.1 in. D/ 161 mm L x 84 mm W x 28 mm DD			
eight	13.3 oz./376 g			
splay	4.7 in. High Definition (1280 x 720); exceptionally bright, outdoor viewable; optically bonded to touch panel			
nager Window	Corning Gorilla Glass			
uchpanel	Dual mode capacitive touch with stylus or bare or gloved fingertip input (conductive stylus sold separately); Corning Gorilla Glass			
acklight	LED backlight			
ower	PowerPrecision/ PowerPrecision+ ² : Improved battery technology for longer cycle times an real-time visibility into battery metrics for better battery management Li-Ion 3.7 V, 4620 mAh typica battery swap function			
Expansion Slot	TC75: User accessible MicroSD up to 32GB SDHC and up to 64 GB SDXC TC75x: User accessible MicroSD up to 32GB SDHC and up to 128 GB SDXC			
IM	2 Nano SIM slot (4FF); 1 Mini SIM/SAM slot (2FF)			
etwork onnections	USB 2.0 High Speed (host and client); WLAN			
otification	Audible tone; multi-color LEDs; vibration			
eypad	On-screen keypad; Enterprise Keyboard			
oice and Audio	Three microphone support with noise cancellation; vibrate alert; speaker; Bluetooth wireless headset support, High quality speaker phone; PTT headset support; Cellular circuit switch voice; HD Voice			
PERFORMANCE	HARACTERISTICS			
PU	TC75: 1.7 GHz dual core processor TC75x: 1.8 GHz hex core 64 bit processor (Snapdragon 650/Android-M)			
perating System	TC75: Android 5.1 Lollipop with Zebra's Mobility Extensions (Mx) TC75x: Android 6.0 Marshmallow with Mx			
l emory	TC75: 1 GB RAM / 8 GB Flash pSLC TC75x: 2 GB RAM / 16 GB Flash pSLC			
SER ENVIRONM	ENT			
perating Temp.	-4° F to 122° F/-20° C to 50°C			
orage Temp.	-40° F to 158° F/-40° C to 70° C			
umidity	5% to 85% non-condensing			
op Specification	8 ft./2.4 m to concrete at room temp. per MIL-STD 810G; 6 ft./1.8 m over the operating temp. range			
umble Specification	2,000 3.2 ft./1.0 m tumbles; meets and exceeds IEC tumble specifications			

Sealing Vibration Thermal Shock Electrostatic	IP65 and IP67 per applicable IEC sealing specifications 4 g's PK Sine (5 Hz to 2 kHz); 0.04g2/Hz Random (20 Hz to 2 kHz); 60 minute duration per axis, 3 axis		
Thermal Shock			
Electrostatic	-40° F to 158° F/-40° C to 70° C rapid transition		
Discharge (ESD)	+/-15kVdc air discharge +/-8kVdc direct discharge +/-8kVdc indirect discharge		
INTERACTIVE SE	NSOR TECHNOLOGY (IST)		
Light Sensor	Automatically adjusts display backlight brightness		
Motion Sensor	eCompass, 3-axis Gyro, 3-axis accelerometer		
DATA CAPTURE			
Scanning	SE4750 imager (1D and 2D); extraordinary range: Scan range – Code 39 barcode: 20 Mil: 1.8 in. to 32.0 in./4.5 cm to 81.3 cm 3 Mil: 3.1 in. to 5.6 in./7.9 cm to 14.2 cm		
Camera	Rear – 8 MP autofocus; f/2.4 aperture (TC75) Rear – 13MP autofocus (TC75x) Front – 1.3 MP fixed focus (TC75/TC75x)		
NFC	TC75: ISO 14443 Type A and B; F; FeliCa, and ISO 15693 cards TC75x: ISO 14443 Type A and B; F; FeliCa, and ISO 15693 cards. P2P mode and Card Emulation via UICC and Host		
WIRELESS WAN	DATA AND VOICE COMMUNICATIONS		
Radio Frequency Band	TC75 Worldwide: LTE: 800/850/900/1800/2100/2600 (FDD 20,5,8,3,1,7) UMTS/HSPA/HSPA+: 850/900/1900/2100; GSM/GPRS/ EDE: 850/900/1800/1900 Americas: LTE: 700/850/1900/AWS/2100 (FDD 17,5,2,4,1); UMTS/ HSPA/HSPA+: 850, 900, AWS, 1900, 2100; GSM/GPRS EDGE: 850/900/1800/1900		
	TC75x Worldwide: LTE: 700,800/850/900/1800/2100/2600 (FDD 28,20,5,8,3,1,7); UMTS/HSPA/HSPA+: 850/900/1900/2100; GSM/GPRS/EDGE: 850/900/1800/1900 Americas: LTE: 700/850/1900/AWS/2100, (FDD 13,12,17,5,26,2,25,4,1); UMTS/HSPA/HSPA+: 850, 900, AWS, 1900, 2100 GSM/GPRS/EDGE: 850/900/1800/1900; CDMA: 850,1900 (BC0,		
GPS	BC10, BC1) TC75: Integrated, Autonomous, Assisted GPS (A-GPS), Navstar, GLONASS TC75x: Integrated, Autonomous, Assisted GPS (A-GPS),		

TC75 Series Specifications (continued)

WIRELESS LAN				
Radio	TC75: IEEE® 802.11a/b/g/n/d/h/i/k/r TC75x: 2x2 MIMO; IEEE 802.11a/b/g/n/ac/d/h/i/r			
Data Rates	TC75 5GHz: 802.11a/n — up to 150 Mbps; 2.4GHz: 802.11b/g/n — up to 72.2 Mbps TC75x 5GHz: 802.11a/n/ac — up to 866.7 Mbps; 2.4GHz: 802.11b/g/n — up to 144 Mbps			
Operating Channels	TC75 Chan 1 - 13 (2412 - 2472 MHz); Chan 36 - 165 (5180 - 5825 MHz) Channel Bandwidth: 20, 40 MHz TC75x Chan 1 - 13 (2412 - 2472 MHz), Chan 36 - 165 (5180 - 5825 MHz), Chan 138, Chan 142 Channel Bandwidth: 20, 40, 80 MHz Actual operating channels/ frequencies depend on regulatory rules and certification agency			
Security and Encryption	WEP (40 or 104 bit); WPA/WPA2 Personal (TKIP, and AES); WPA/WPA2 Enterprise (TKIP and AES) — EAP- TTLS (PAP, MSCHAP, MSCHAPv2), EAP-TLS, PEAPv0- MSCHAPv2, PEAPv1-EAP-GTC, EAP Fast ³ and LEAP			
Features	TC75: Wi-Fi Multimedia [™] (WMM), Soft AP, Wi-Fi Direct, Miracast TC75x: Wi-Fi Multimedia (WMM), Soft AP, MIMO with 2 Spatial Streams, 256 QAM Modulation on 56 GHz radio; Maximum Ratio Combining (MRC), Tx/Rx Low-Density Parity Check (LDPC), Transmit Beamforming(TxBF) and Beamformee (BFee) capability, Full IEEE 802.11 a/b/g/n legacy compatibility			
Certifications	TC75: WFA (802.11n, WMM-PS, Wi-Fi Direct, WPS, Miracast) TC75x: WFA (802.11n, WMM-PS)			
Fast Roam	PMKID caching, Cisco CCKM, 802.11r, OKC			
	1			

Bluetooth		Class 2, Bluetooth v4.0 (Bluetooth® Smart technology) BT Wideband support HFPv1.6 Bluetooth v4.1 LE (TC75x only)			
сомм	IUNICATIO	N AND ME	SSAGIN	١G	
Connect talk solu radio int TC75 Se	PTT) small grou PTT Pro (suppo tion which also egration. Work	p communica orted) provid includes me force Connec as a full feat	ations acro es a scala ssaging, l ct Voice cli	ded) provides instant push-to-tall oss Wi-Fi networks. Workforce ble network agnostic push-to- ocation services and two-way ient (supported) enables the le telephone with multi-line	
ADDIT	IONAL MOI	BILITY DN	A SOLU	TIONS	
X	computers by and managem	adding functi ient of our mo	ionality as obile devic	nore value out of our mobile well as simplifying deployment es. For more information on these v.zebra.com/mobilitydna	
	Enterprise K	eyboard		Enterprise Home Screen	
	Stage Now			AppGallery	
	EMDK			Enterprise Browser	
	SimulScan				
Available	e Mobility DNA	features may	vary by m	nodel.	
WARR	ANTY				
is warra (one) yea	nted against de	efects in work e of shipment	(manship a t. For com	anty statement, the TC75 Series and materials for a period of 1 plete warranty statement, please	
RECO	MMENDED	SERVICES	5		

1. Magnetic Stripe Reader not supported on TC75x.

2. PowerPrecision+ batteries are available only on TC75x models and provide advanced state of health and advanced state of charge metrics.

3. EAP Fast supported on TC75 models only.

Specifications subject to change without notice and some features may vary by model.



reddot award 2016 winner industrial design





NA and Corporate Headquarters +1 800 423 0442 inquiry4@zebra.com Asia-Pacific Headquarters +65 6858 0722 contact.apac@zebra.com EMEA Headquarters zebra.com/locations mseurope@zebra.com Latin America Headquarters +1 847 955 2283 la.contactme@zebra.com

©2016 ZIH Corp and/or its affiliates. All rights reserved. Zebra and the stylized Zebra head are trademarks of ZIH Corp registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. Part number: SS-TC75 09/2016